




ADVANCED MATERIALOGRAPHY

CONSUMABLES 2020

Cutting | Mounting | Grinding, Polishing, Etching | Analyzing





SCIENCE FOR SOLIDS

HEAT TREATMENT
ELEMENTAL ANALYSIS
MATERIALOGRAPHY &
HARDNESS TESTING
MILLING & SIEVING
PARTICLE CHARACTERIZATION

As part of the VERDER Group, the business division VERDER SCIENTIFIC sets standards in the development, manufacture and sales of laboratory and analytical equipment. The instruments are used in the areas of quality control, research and development for sample preparation and analysis of solids.

ATM – Machines Are Our Passion

Machines and equipment for the materialographic laboratory “Made in Germany”

Whatever you need for quality testing and material analysis, ATM has it all: As a manufacturer of high-quality machines for materialography (metallography), we offer the most comprehensive solution for your needs. We not only supply a wide range of instruments but also accessories, consumables, complete laboratories and tailor-made special-purpose solutions.

Our innovative cut-off machines, mounting presses, grinders, polishers/electrolytic etchers, as well as hardness testers and analysis systems provide maximum reliability and flexibility. Thanks to the most advanced engineering technologies and manufacture of components in our own factory, we are able to fulfill individual customer requirements by adapting our instruments to their needs.

Our R&D department for hard- and software works in close cooperation with our customers to ensure continuous optimization of our products. Customers in more than 30 countries appreciate our comprehensive sales and service network as well as direct communication with our experts.

To provide you with solutions of consistently high quality we rely on the expertise and creativity of our qualified and dedicated long-standing employees.

ATM offers:

- **Modern production engineering and high vertical integration:**
Optimum control of every single component of our machines guarantees unrivaled ATM product quality “made in Germany”.
- **Application consultation and end-user seminars with individual focus:**
Our application experts ascertain parameters and instrument configurations best suited for preparation of your sample material.
- **In-house software and hardware development:**
ATM hosts the complete R&D process in-house making customer-specific solutions and adaptations to individual requirements our great strength.



www.atm-m.com

ATM Contact

ATM is a provider of integrated solutions. In addition to our comprehensive product range we offer full application support and technical service.

ATM GmbH
Emil-Reinert-Str. 2
57636 Mammelzen
Germany

Phone: +49 (0) 2681-9539-0
Fax: +49 (0) 2681-9539-20

info@atm-m.com
www.atm-m.com



PREMIUM QUALITY

MADE IN GERMANY


Exhibitions 2020

■ Germany

CONTROL Stuttgart
05. – 08. May 2020

Härterei Kongress Köln
20. – 22. October 2020

FormNext
10. – 13. November 2020



To find the complete list of dates and events, please visit our website at www.atm-m.com/news/dates-events/.
ATM exhibits its products at various international trade shows and conferences and also host inhouse seminars.

Excellent sales and service network throughout the world



Our comprehensive network of distributors and agents provides expert advice on products and applications throughout the world as well as technical service. For detailed information please refer to our website www.atm-m.com

General

About us	3
Contact information	4
ATM Worldwide	5
General Terms and Conditions of Business and Delivery	74-75
Index	76-77
Expiry dates of consumables	79



Cut-off wheels for precision cut-off machines



Corundum cut-off wheels for precision cut-off machines	10
Diamond cut-off wheels for precision cut-off machines	10
Diamond cup grinder	11
CBN cut-off wheels for precision cut-off machines	11

Cut-off wheels for wet abrasive cut-off machines



Premium cut-off wheels for wet abrasive cut-off machines	12-13
Corundum cut-off wheels for wet abrasive cut-off machines	13
Diamond cut-off wheels for wet abrasive machines	14
CBN cut-off wheels for wet abrasive machines	14
Accessories for cut-off wheels	14

Accessories & equipment for cutting



Anti corrosion coolant	15
ATM-CoolCut	15
Cooling agent additives	15
Accessories for maintenance and care of coolants	16
Accessories for cut-off machines	16

Accessories for filter systems



Filter fleece for belt filter systems	17
Filter fleece mat for recirculation cooling systems	17
Filter inserts	17



Hot mounting material



Accessories for hot mounting	20
Hot mounting material	21

Cold mounting material



Infiltration set	22
Infiltration unit	22
Pressure unit	22
Cold mounting material methacrylate	23
Cold mounting material MMA-free	24
Cold mounting material epoxy resin	24
Cold mounting material methylmethacrylate	24
Accessories for cold mounting	25
Cold mounting moulds	25



Solution Boxes / Planar grinding



Solution Boxes	28-29
Planar grinding stone for Saphir 375	30

Grinding



NEW: POLARIS SIC grinding discs	31
NEW: POLARIS M diamond grinding discs	32
NEW: POLARIS H diamond grinding discs	33
NEW: QUASAR diamond grinding discs	34
NEW: VEGA diamond grinding discs	35
GALAXY diamond grinding discs	36
NEW: GALAXY fine grinding disc Contero S	37
GALAXY fine grinding disc Contero H	37
Diamond grinding foils, metal bond	38
Zirconia aluminum oxid grinding papers for coarse grinding	38
Silicon carbide grinding foils	39

Adhere carrier discs, double-sided	40
Alumina grinding foils	40
Silicon carbide grinding paper, with foil reverse back	41-42
Silicon carbide grinding papers	42-45
Clamping rings	44
Double-sided adhesive foils	45
Grinding papers for Saphir 300 (mobile grinder and polisher)	46
Silicon carbide grinding belts	46

Polishing



Dia-COMplete Poly, All-In-One Diamond suspension, water-based	47
NEW: Dia-COMplete Poly+, All-In-One Diamond suspension, water-based	48
Dia-COMplete Mono, All-In-One Diamond suspension, water-based	49
NEW: Dia-COMplete Mono+, All-In-One Diamond suspension, water-based	50
Diamond suspension polycrystalline	51
NEW: Diamond suspension polycrystalline+	52
Diamond suspension monocrystalline	53
NEW: Diamond suspension monocrystalline+	54-55
Diamond suspension (alcohol-based) polycrystalline	56
Diamond suspension (alcohol-based) monocrystalline	56
Diamond suspension (oil-based) polycrystalline	56
Diamond suspension (oil-based) monocrystalline	56
Diamond spray polycrystalline	57
Diamond paste polycrystalline	57
Diamond paste monocrystalline	57
NEW: Diamond stick monocrystalline	57
Diamond lubricant	58
Alumina suspension, calcinated	59
Fine polishing suspensions	59
GALAXY Polishing cloths with metal back for diamond polishing	60-61
Polishing cloths, self-adhesive	62-63
Polishing cloth carrier discs	64
Carrier plate	64
Magnetic foil, self-adhesive	64

Etching



Electrolytes	65
Accessories for Kristall 650	65
Etchants	66



Microscopy/Analysis



Accessories for microscopy	70
Iron-carbon-diagram	70
Cleaning agents for ultrasonic cleaner	71
Cleaning aids	71
Assembly cleaner	71

Accessories for Microscopy/Analysis



Accessories	72
Storage of samples	72
Safety equipment for etching	73
Pane cleaning for fume cupboard	73
Replication set	73
Precision replication material	73

Disclaimer

- We reserve the right to effect technical changes as well as price adjustments due to technical progress. All listings in our price list are based on our General Terms for Delivery and Payment.
- This price list covers only the current versions of products.
- The images may show accessories which may not be part of the standard delivery scope.
- Our warranty period is product related.
- All prices are ex works, including packaging.
ATM price list 2020/E, valid from 1st January 2020 to 31st December 2020

www.atm-m.com





Cutting

Cut-off wheels for precision cut-off machines



Corundum cut-off wheels for precision cut-off machines	10
Diamond cut-off wheels for precision cut-off machines	10
Diamond cup grinder	11
CBN cut-off wheels for precision cut-off machines	11

Cut-off wheels for wet abrasive cut-off machines



Premium cut-off wheels for wet abrasive cut-off machines	12-13
Corundum cut-off wheels for wet abrasive cut-off machines	13
Diamond cut-off wheels for wet abrasive machines	14
CBN cut-off wheels for wet abrasive machines	14
Accessories for cut-off wheels	14

Accessories & equipment for cutting



Anti corrosion coolant	15
ATM-CoolCut	15
Cooling agent additives	15
Accessories for maintenance and care of coolants	16
Accessories for cut-off machines	16

Accessories for filter systems



Filter fleece for belt filter systems	17
Filter fleece mat for recirculation cooling systems	17
Filter inserts	17



Item No.	Unit	Description		
Corundum cut-off wheels for precision cut-off machines				
		Ø	Thickness	Arbor Size
» fine-grained for universal application » for materials of higher hardness				
92002643	5 Pcs.	100 mm	0.25 mm	12.7 mm
92002644	5 Pcs.	125 mm	0.45 mm	12.7 mm
92002769	5 Pcs.	150 mm	0.45 mm	12.7 mm
» coarse-grained for universal application » for materials of lower hardness and mounted samples				
92002645	5 Pcs.	100 mm	0.4 mm	12.7 mm
92002646	5 Pcs.	125 mm	0.8 mm	12.7 mm
92002770	5 Pcs.	150 mm	0.6 mm	12.7 mm
92002647	5 Pcs.	200 mm	0.8 mm	12.7 mm
92004159	5 Pcs.	150 mm	1 mm	12.7 mm
92004998	5 Pcs.	150 mm	1 mm	20 mm (incl. reduction ring 12.7 mm*)
92004155	5 Pcs.	200 mm	1.5 mm	12.7 mm
* 1 reduction ring 12.7 mm for each order				
Reduction ring 12.7 mm				
01304330	1 Pcs.	20 mm		
Diamond cut-off wheels for precision cut-off machines				
		Ø	Thickness	Arbor Size
» for universal application				
92002397	1 Pcs.	76 mm	0.3 mm	12.7 mm
92002401	1 Pcs.	102 mm	0.3 mm	12.7 mm
92002405	1 Pcs.	127 mm	0.5 mm	12.7 mm
92002409	1 Pcs.	152 mm	0.5 mm	12.7 mm
» for glass, ceramics, rocks				
92002398	1 Pcs.	76 mm	0.3 mm	12.7 mm
92002402	1 Pcs.	102 mm	0.3 mm	12.7 mm
92002406	1 Pcs.	127 mm	0.5 mm	12.7 mm
92002410	1 Pcs.	152 mm	0.5 mm	12.7 mm
95015121	1 Pcs.	200 mm	1.0 mm	12.7 mm
» for hard metals				
92002400	1 Pcs.	76 mm	0.3 mm	12.7 mm
92002404	1 Pcs.	102 mm	0.3 mm	12.7 mm
92002408	1 Pcs.	127 mm	0.5 mm	12.7 mm
92002412	1 Pcs.	152 mm	0.5 mm	12.7 mm
» for plastic, rubber on request				



Item No.	Unit	Description																								
Diamond cup grinder																										
		<table border="1"> <thead> <tr> <th>Ø</th> <th>Thickness</th> <th>Height</th> <th>Arbor Size</th> <th>Bond</th> </tr> </thead> <tbody> <tr> <td colspan="5" style="text-align: center;">» for glass fiber-reinforced boards</td> </tr> <tr> <td>92008573</td> <td>1 Pcs.</td> <td>100 mm</td> <td>8 mm</td> <td>35 mm</td> <td>12.7 mm</td> <td>galvanic</td> </tr> <tr> <td>92006607</td> <td>1 Pcs.</td> <td>150 mm</td> <td>8 mm</td> <td>35 mm</td> <td>12.7 mm</td> <td>galvanic</td> </tr> </tbody> </table>	Ø	Thickness	Height	Arbor Size	Bond	» for glass fiber-reinforced boards					92008573	1 Pcs.	100 mm	8 mm	35 mm	12.7 mm	galvanic	92006607	1 Pcs.	150 mm	8 mm	35 mm	12.7 mm	galvanic
Ø	Thickness	Height	Arbor Size	Bond																						
» for glass fiber-reinforced boards																										
92008573	1 Pcs.	100 mm	8 mm	35 mm	12.7 mm	galvanic																				
92006607	1 Pcs.	150 mm	8 mm	35 mm	12.7 mm	galvanic																				



Diamond cup grinder																										
		<table border="1"> <thead> <tr> <th>Ø</th> <th>Thickness</th> <th>Arbor Size</th> <th>Bond</th> <th>Grain Size</th> </tr> </thead> <tbody> <tr> <td colspan="5" style="text-align: center;">» for glass, ceramics, rocks, hard metal</td> </tr> <tr> <td>95015122</td> <td>1 Pcs.</td> <td>150 mm</td> <td>21.5 mm</td> <td>12.7 mm</td> <td>resin</td> <td>fine</td> </tr> <tr> <td>95015123</td> <td>1 Pcs.</td> <td>150 mm</td> <td>21.5 mm</td> <td>12.7 mm</td> <td>resin</td> <td>coarse</td> </tr> </tbody> </table>	Ø	Thickness	Arbor Size	Bond	Grain Size	» for glass, ceramics, rocks, hard metal					95015122	1 Pcs.	150 mm	21.5 mm	12.7 mm	resin	fine	95015123	1 Pcs.	150 mm	21.5 mm	12.7 mm	resin	coarse
Ø	Thickness	Arbor Size	Bond	Grain Size																						
» for glass, ceramics, rocks, hard metal																										
95015122	1 Pcs.	150 mm	21.5 mm	12.7 mm	resin	fine																				
95015123	1 Pcs.	150 mm	21.5 mm	12.7 mm	resin	coarse																				

CBN cut-off wheels for precision cut-off machines																																									
		<table border="1"> <thead> <tr> <th>Ø</th> <th>Thickness</th> <th>Arbor Size</th> </tr> </thead> <tbody> <tr> <td colspan="3" style="text-align: center;">» for composites and rigid materials</td> </tr> <tr> <td>92002442</td> <td>1 Pcs.</td> <td>76 mm</td> <td>0.9 mm</td> <td>12.7 mm</td> </tr> <tr> <td>92002443</td> <td>1 Pcs.</td> <td>102 mm</td> <td>0.5 mm</td> <td>12.7 mm</td> </tr> <tr> <td>92002444</td> <td>1 Pcs.</td> <td>127 mm</td> <td>0.5 mm</td> <td>12.7 mm</td> </tr> <tr> <td>92002445</td> <td>1 Pcs.</td> <td>153 mm</td> <td>0.65 mm</td> <td>12.7 mm</td> </tr> <tr> <td>92002446</td> <td>1 Pcs.</td> <td>178 mm</td> <td>0.9 mm</td> <td>12.7 mm</td> </tr> <tr> <td>92006419</td> <td>1 Pcs.</td> <td>200 mm</td> <td>0.5 mm</td> <td>12.7 mm</td> </tr> <tr> <td colspan="3" style="text-align: center;">» other diameters on request</td> </tr> </tbody> </table>	Ø	Thickness	Arbor Size	» for composites and rigid materials			92002442	1 Pcs.	76 mm	0.9 mm	12.7 mm	92002443	1 Pcs.	102 mm	0.5 mm	12.7 mm	92002444	1 Pcs.	127 mm	0.5 mm	12.7 mm	92002445	1 Pcs.	153 mm	0.65 mm	12.7 mm	92002446	1 Pcs.	178 mm	0.9 mm	12.7 mm	92006419	1 Pcs.	200 mm	0.5 mm	12.7 mm	» other diameters on request		
Ø	Thickness	Arbor Size																																							
» for composites and rigid materials																																									
92002442	1 Pcs.	76 mm	0.9 mm	12.7 mm																																					
92002443	1 Pcs.	102 mm	0.5 mm	12.7 mm																																					
92002444	1 Pcs.	127 mm	0.5 mm	12.7 mm																																					
92002445	1 Pcs.	153 mm	0.65 mm	12.7 mm																																					
92002446	1 Pcs.	178 mm	0.9 mm	12.7 mm																																					
92006419	1 Pcs.	200 mm	0.5 mm	12.7 mm																																					
» other diameters on request																																									

Machine and blade compatibility

Cut-off machine	Arbor size	Ø (max.)
Brillant 200	32 mm	254 mm/10"
Brillant 210	12.7 mm	203 mm/8"
Brillant 220	12.7 mm	203 mm/8"
Brillant 230	32 mm	254 mm/10" 305 mm/12"
Brillant 240	32 mm	254 mm/10"
Brillant 250	32 mm	305 mm/12" 356 mm/14"
Brillant 255	32 mm	356 mm/14" 406 mm/16"
Brillant 265	32 mm	356 mm/14" 406 mm/16"
Brillant 275	32 mm	432 mm/17" 508 mm/20"
Brillant 3D	32 mm	432 mm/17" 508 mm/20"
Brillant 285	32 mm	508 mm/20" 610 mm/24"
Brillant 2000	32 mm	610 mm/24" 813 mm/32"





Cut-off wheel selection according to material hardness

Type description		Rubber bonded										
Type description	B	for high-speed steels, heat-treated steels, non-corrosive steels								400-700 HV		
	A	50-500 HV Universal wheel, soft and hard metals, Superalloys										
Type description		Resin bonded										
Type description	FS-	E	very hard, ferrous metals								>550 HV	
		D	hard, ferrous metals								400-700 HV	
		C	medium hard, ferrous metals								300-550 HV	
		B	medium soft, ferrous metals								200-450 HV	
	A	soft, ferrous metals (30-300 HV)										
	Ti-	A	ductile metals									
	NF-	A	non-ferrous metals									
		soft		medium soft		medium hard		hard		very hard		
HV		30	50	80	120	180	250	350	500	700	940	
HRC							22	36	49	60	68	

ATM type description	
old	new
C	FS-E
D	FS-D
H	FS-C
E, I	FS-B
E, I	FS-A
F	Ti-A
E	NF-A

Item No.	Unit	Description
----------	------	-------------

Premium cut-off wheels for wet abrasive cut-off machines

		Ø	Thickness	Arbor Size	Bond	Type
NF-A - for non-ferrous metals (30-300HV)						
95012531	10 Pcs.	250 mm	1.5 mm	32 mm	SiC / Resin	NF-A, Purple
95012538	10 Pcs.	300 mm	2.0 mm	32 mm	SiC / Resin	NF-A, Purple
95012545	10 Pcs.	350 mm	2.5 mm	32 mm	SiC / Resin	NF-A, Purple
95012552	10 Pcs.	400 mm	3.0 mm	32 mm	SiC / Resin	NF-A, Purple
95012566	5 Pcs.	500 mm	4.0 mm	32 mm	SiC / Resin	NF-A, Purple
95012573	5 Pcs.	600 mm	4.5 mm	32 mm	SiC / Resin	NF-A, Purple
Ti-A - for Titanium and alloys, refractory metals						
95012530	10 Pcs.	250 mm	1.5 mm	32 mm	SiC / Resin	Ti-A, Pink
95012537	10 Pcs.	300 mm	2.0 mm	32 mm	SiC / Resin	Ti-A, Pink
95012544	10 Pcs.	350 mm	2.5 mm	32 mm	SiC / Resin	Ti-A, Pink
95012551	10 Pcs.	400 mm	3.0 mm	32 mm	SiC / Resin	Ti-A, Pink
95012565	5 Pcs.	500 mm	4.0 mm	32 mm	SiC / Resin	Ti-A, Pink
95012572	5 Pcs.	600 mm	4.5 mm	32 mm	SiC / Resin	Ti-A, Pink
FS-A - for soft steel (30-300HV), non-ferrous metals, polymer						
95012529	10 Pcs.	250 mm	1.5 mm	32 mm	Al2O3 / Resin	FS-A, Red
95012536	10 Pcs.	300 mm	2.0 mm	32 mm	Al2O3 / Resin	FS-A, Red
95012543	10 Pcs.	350 mm	2.5 mm	32 mm	Al2O3 / Resin	FS-A, Red
95012550	10 Pcs.	400 mm	3.0 mm	32 mm	Al2O3 / Resin	FS-A, Red
95012564	5 Pcs.	500 mm	4.0 mm	32 mm	Al2O3 / Resin	FS-A, Red
95012571	5 Pcs.	600 mm	4.5 mm	32 mm	Al2O3 / Resin	FS-A, Red
FS-B - for medium soft steel (200-450HV)						
95012528	10 Pcs.	250 mm	1.5 mm	32 mm	Al2O3 / Resin	FS-B, Orange
95012535	10 Pcs.	300 mm	2.0 mm	32 mm	Al2O3 / Resin	FS-B, Orange
95012542	10 Pcs.	350 mm	2.5 mm	32 mm	Al2O3 / Resin	FS-B, Orange
95012549	10 Pcs.	400 mm	3.0 mm	32 mm	Al2O3 / Resin	FS-B, Orange
95012563	5 Pcs.	500 mm	4.0 mm	32 mm	Al2O3 / Resin	FS-B, Orange
95012570	5 Pcs.	600 mm	4.5 mm	32 mm	Al2O3 / Resin	FS-B, Orange





Item No.	Unit	Description				
Premium cut-off wheels for wet abrasive cut-off machines						
		Ø	Thickness	Arbor Size	Bond	Type
FS-C - for medium hard steel (300-550HV), case hardened, nitrided steels						
95012527	10 Pcs.	250 mm	1.5 mm	32 mm	Al2O3 / Resin	FS-C, Yellow
95012534	10 Pcs.	300 mm	2.0 mm	32 mm	Al2O3 / Resin	FS-C, Yellow
95012541	10 Pcs.	350 mm	2.2 mm	32 mm	Al2O3 / Resin	FS-C, Yellow
95012548	10 Pcs.	400 mm	3.0 mm	32 mm	Al2O3 / Resin	FS-C, Yellow
95012562	5 Pcs.	500 mm	4.0 mm	32 mm	Al2O3 / Resin	FS-C, Yellow
95012569	5 Pcs.	600 mm	4.5 mm	32 mm	Al2O3 / Resin	FS-C, Yellow
FS-D - for hard steels (400-700HV), annealed, carburised steels						
95012526	10 Pcs.	250 mm	1.5 mm	32 mm	Al2O3 / Resin	FS-D, Green
95012533	10 Pcs.	300 mm	2.0 mm	32 mm	Al2O3 / Resin	FS-D, Green
95012540	10 Pcs.	350 mm	2.5 mm	32 mm	Al2O3 / Resin	FS-D, Green
95012547	10 Pcs.	400 mm	3.0 mm	32 mm	Al2O3 / Resin	FS-D, Green
95012561	5 Pcs.	500 mm	4.0 mm	32 mm	Al2O3 / Resin	FS-D, Green
95012568	5 Pcs.	600 mm	4.5 mm	32 mm	Al2O3 / Resin	FS-D, Green
FS-E - for very hard steels (>550HV)						
95012525	10 Pcs.	250 mm	1.5 mm	32 mm	Al2O3 / Resin	FS-E, Blue
95012532	10 Pcs.	300 mm	2.0 mm	32 mm	Al2O3 / Resin	FS-E, Blue
95012539	10 Pcs.	350 mm	2.5 mm	32 mm	Al2O3 / Resin	FS-E, Blue
95012546	10 Pcs.	400 mm	3.0 mm	32 mm	Al2O3 / Resin	FS-E, Blue
95012560	5 Pcs.	500 mm	4.0 mm	32 mm	Al2O3 / Resin	FS-E, Blue
95012567	5 Pcs.	600 mm	4.5 mm	32 mm	Al2O3 / Resin	FS-E, Blue

ATM type description	
old	new
C	FS-E
D	FS-D
H	FS-C
E, I	FS-B
E, I	FS-A
F	Ti-A
E	NF-A

Corundum cut-off wheels for wet abrasive cut-off machines						
		Ø	Thickness	Arbor Size	Bond	Type
C - Universal wheel for materials of high to very high hardness						
92001550	10 Pcs.	235 mm	1.5 mm	32 mm	Resin	C
92001554	10 Pcs.	250 mm	1.5 mm	32 mm	Resin	C
92001558	10 Pcs.	300 mm	2 mm	32 mm	Resin	C
92001669	10 Pcs.	350 mm	2 mm	32 mm	Resin	C
92001783	10 Pcs.	400 mm	3 mm	32 mm	Resin	C
D - Universal wheel for medium hard materials, case-hardened steels						
92001551	10 Pcs.	235 mm	1.5 mm	32 mm	Resin	D
92001555	10 Pcs.	250 mm	1.5 mm	32 mm	Resin	D
92001559	10 Pcs.	300 mm	2 mm	32 mm	Resin	D
92001670	10 Pcs.	350 mm	2 mm	32 mm	Resin	D
92001784	10 Pcs.	400 mm	3 mm	32 mm	Resin	D
E - for soft steels, non-ferrous-materials, plastics						
92001552	10 Pcs.	235 mm	1.5 mm	32 mm	Resin	E
92001556	10 Pcs.	250 mm	1.5 mm	32 mm	Resin	E
92001560	10 Pcs.	300 mm	2 mm	32 mm	Resin	E
92001671	10 Pcs.	350 mm	2.2 mm	32 mm	Resin	E
92001785	10 Pcs.	400 mm	3 mm	32 mm	Resin	E
F - for titanium and titanium alloys						
92002417	10 Pcs.	230 mm	1.5 mm	32 mm	Resin	F
92002425	10 Pcs.	250 mm	1.5 mm	32 mm	Resin	F
92002426	10 Pcs.	300 mm	2 mm	32 mm	Resin	F
92002427	10 Pcs.	350 mm	2.5 mm	32 mm	Resin	F
92002428	10 Pcs.	400 mm	3 mm	32 mm	Resin	F
I - for construction steels and cast material						
92006066	10 Pcs.	250 mm	1.6 mm	32 mm	Resin	I
92005863	10 Pcs.	300 mm	2 mm	32 mm	Resin	I
92005862	10 Pcs.	350 mm	2.5 mm	32 mm	Resin	I
92008504	10 Pcs.	400 mm	3 mm	32 mm	Resin	I





Item No.	Unit	Description
Corundum cut-off wheels for wet abrasive cut-off machines		
Ø	Thickness	Arbor Size Bond Type
A - Universal wheel, soft and hard metals, Superalloys		
92002413	10 Pcs.	229 mm 0.8 mm 32 mm Rubber A
92002599	10 Pcs.	254 mm 1 mm 32 mm Rubber A
92002441	10 Pcs.	305 mm 1 mm 32 mm Rubber A
92002436	10 Pcs.	356 mm 1.6 mm 32 mm Rubber A
92002439	10 Pcs.	406 mm 1.6 mm 32 mm Rubber A
92008537	10 Pcs.	500 mm 2.4 mm 32 mm Rubber A
92004007	10 Pcs.	600 mm 4.3 mm 40 mm Rubber A
B - for high-speed steels, heat-treated steels, non-corrosive steels		
92002414	10 Pcs.	229 mm 1.6 mm 32 mm Rubber B
92002600	10 Pcs.	254 mm 1.6 mm 32 mm Rubber B
92002434	10 Pcs.	305 mm 1.6 mm 32 mm Rubber B
92002437	10 Pcs.	356 mm 2.4 mm 32 mm Rubber B
92002440	10 Pcs.	406 mm 2.4 mm 32 mm Rubber B
92008874	10 Pcs.	500 mm 3 mm 32 mm Rubber B
Diamond cut-off wheels for wet abrasive machines		
Ø	Thickness	Arbor Size Bond
» for ceramic materials		
92002450	1 Pcs.	230 mm 1.2 mm 32 mm Bronze
92002452	1 Pcs.	250 mm 1.2 mm 32 mm Bronze
92002453	1 Pcs.	300 mm 1.6 mm 32 mm Bronze
» for hard metals, generally for materials of high hardness		
92002451	1 Pcs.	250 mm 1.2 mm 32 mm Resin
92002454	1 Pcs.	300 mm 1.6 mm 32 mm Resin
» for composite materials (hard/soft combinations)		
92004719	1 Pcs.	300 mm 1.3 mm 32 mm Bronze
other diameters on request		
CBN cut-off wheels for wet abrasive machines		
Ø	Thickness	Arbor Size
» for Nickel and Cobalt based alloys		
92002456	1 Pcs.	250 mm 1.6 mm 32 mm
92002457	1 Pcs.	300 mm 1.6 mm 32 mm
Accessories for cut-off wheels		
Dressing stone		
92002460	1 Pcs.	Dressing stone for diamond cut-off wheels, CBN cut-off wheels and cup wheels



Item No.	Unit	Description
Anti corrosion coolant for wet abrasive cut-off machines » for steel, cast iron, non-ferrous metal		
95014280	1 l	concentrate (ratio 1:35) / refractometer: 1.4%/°Bx
95014281	5 l	concentrate (ratio 1:35) / refractometer: 1.4%/°Bx
95014282	10 l	concentrate (ratio 1:35) / refractometer: 1.4%/°Bx

ATM-CoolCut, environment- and user-friendly free of oil, boron, nitride and formaldehyde » for steel, cast iron, light and non-ferrous metal, glass and ceramics, composites good anti-corrosion protection and cutting properties		
95004145	1 l	ATM-CoolCut (mixing ratio 1:25 (4%) - 1:12.5 (8%) / refractometer: 2.0%/°Bx
95004146	5 l	ATM-CoolCut (mixing ratio 1:25 (4%) - 1:12.5 (8%) / refractometer: 2.0%/°Bx
95004147	10 l	ATM-CoolCut (mixing ratio 1:25 (4%) - 1:12.5 (8%) / refractometer: 2.0%/°Bx

Cooling agent additives ATM-CoolAdd NF		
92006504	1 kg	ATM-CoolAdd NF, additive for cutting of hard metals, c-steels, copper alloys (prevents dilution of cobalt or chrome) Mixing concentration in aqueous coolant approx. 0.1 - 0.3%

ATM-CoolAdd CU		
95008731	1 l	ATM-CoolAdd CU, additive for cutting of non-ferrous materials like Cu and its alloys. Mixing concentration in aqueous coolant approx. 0.05 - 0.2%


ATM-CoolClean B		
95006593	1 kg	ATM-CoolClean B, bactericide for cooling lubricants (prevents contamination by a wide range of bacteria) Mixing concentration in aqueous coolant approx. 0.1 - 0.2%

Defoaming agent		
92006503	200 ml	Defoaming agent, additive for water-based coolants Mixing concentration in aqueous coolant approx. 0.005 - 0.05%
92006506	1 l	Defoaming agent, additive for water-based coolants Mixing concentration in aqueous coolant approx. 0.005 - 0.05%

» Download of Safety Data Sheets at
<http://www.atm-m.com/products/consumables>

Info Coolants

Additional informations about the handling and maintenance of coolants are available in our "ATM-CoolCut" manual






Item No.	Unit	Description
Accessories for maintenance and care of coolants		
Maintenance and testing set		
95007866	1 Pcs.	Maintenance and testing set for anti-corrosion coolant (case with handheld refractometer, plastic cup for extraction of sample, test strips, thermometer)
Accessories for maintenance and testing set		
92005616	100 Pcs.	pH test strips
92005613	100 Pcs.	Nitrate test strips
92005614	100 Pcs.	Nitrite test strips
95007865	100 Pcs.	Water hardness test strips
ATM-PreClean		
92006502	1 kg	ATM-PreClean, disinfection system cleaner for cleaning the coolant circulation system before exchanging coolant
Accessories for maintenance and care of cut-off machines		
Corrosion protection- and care spray		
95001749	400 ml	Corrosion protection- and care spray, fully synthetical, silicon-free corrosion protection oil, for metal surfaces (e.g. clamping vices)
Anti-fog spray		
95008900	100 ml	Anti-fog spray (prevents steaming up the viewing window by splash water)
» Download of Safety Data Sheets at http://www.atm-m.com/products/consumables		



Item No.	Unit	Description	
Filter fleece for belt filter systems			
Length x Width			
» for belt filter system BFA 165			
92008745	1 Pcs.	Filter fleece roll, fine, 100 µm	100 m x 450 mm
» for belt filter system BFA 325			
92008744	1 Pcs.	Filter fleece roll, coarse, 150 µm	100 m x 450 mm
» for belt filter system BFA 285			
92008780	1 Pcs.	Filter fleece roll, coarse, 150 µm	100 m x 710 mm
» for belt filter system BFA 100/130			
95001696	1 Pcs.	Filter fleece roll, coarse, 150 µm	100 m x 420 mm
» other sizes on request			

Filter fleece mat for recirculation cooling systems			
Length x Width			
» for Brillant 2000			
95007753	1 Pcs.	Filter fleece mat	940 x 720 mm
» for Brillant 285			
95007761	1 Pcs.	Filter fleece mat	724 x 720 mm
» for recirculation cooling system 15 Ltr.			
95014816	1 Pcs.	Filter fleece mat	235 x 148 mm

Filter inserts			
Dimensions			
» for Brillant 255/265/270/275/280			
92008739	1 Pcs.	Filter cloth and fleece	490 x 290 x 190 mm
» for recirculation cooling system 45 Ltr.			
92008741	1 Pcs.	Filter cloth and fleece	290 x 150 x 190 mm (until year of construction 2012)
95007759	1 Pcs.	Filter cloth and fleece	250 x 200 x 155 mm (from year of construction 2013)
» for settling tank			
92005993	1 Pcs.	Fleece	290 x 150 x 190 mm (until year of construction 2012)
95007760	1 Pcs.	Fleece	250 x 200 x 155 mm (from year of construction 2013)







Mounting

Hot mounting material



Accessories for hot mounting	20
Hot mounting material	21

Cold mounting material



Infiltration set	22
Infiltration unit	22
Pressure unit	22
Cold mounting material methacrylate	23
Cold mounting material MMA-free	24
Cold mounting material epoxy resin	24
Cold mounting material methylmethacrylate	24
Accessories for cold mounting	25
Cold mounting moulds	25





Properties of hot mounting materials

Mounting material	Recommended Application	Basis/ Filler	Hardness (Shore D)	Removal rate (grindability)
Bakelite (black, red, green)	Routine work, soft to medium-hard materials, good for padding	Phenolic resin/ wood flour	92	medium
EPO black	High edge retention, edge examination, medium-hard to hard materials	epoxy resin/ mineral and glass fibre	93	very low
EPO-Max	High edge retention, edge examination, medium-hard to hard materials, easy cleaning of mould and ram due to low adhesion	Epoxy resin/ mineral	93	very low
Duroplast black	Conductive, SEM-analysis, electrolytic polishing	Phenolic resin/ graphite	89	medium
Duroplast blue	High edge retention, edge examination, soft to medium-hard materials, recommended for grinding stones	Phenolic resin/ glass fiber	92	low
Thermoplast	Transparent mounting, targeted preparation, good for padding, marking	Acrylic resin	86	medium

Item No.	Unit	Description
Accessories for hot mounting		
Accessories for hot mounting		
92002660	90 ml	Silicon paste, anti-stick agent
92002661	200 ml	Silicon spray, anti-stick agent
92004441	1 Pcs.	Brass brush for cleaning of hot mounting press
92002658	1 Pcs.	Funnel for hot mounting material
92002715	1 Pcs.	Square bottle with screw-top for approx. 1 ltr. mounting material
92002657	100 Pcs.	Angle adapter for angled polishing, 10°
92001716	10 Pcs.	Dosing spoon for hot and cold mounting material, 13 ml
92002662	100 Pcs.	Steel clip for for aligning thin samples in mould
92002663	100 Pcs.	Plastic clip for aligning thin samples in mould, transparent
92002707	100 Pcs.	Plastic clip for aligning thin samples in mould, black
92002708	100 Pcs.	Plastic clip for aligning thin samples in mould, red
92002709	100 Pcs.	Plastic clip for aligning thin samples in mould, grey



Item No.	Unit	Description
Hot mounting material		
<div style="display: flex; justify-content: center; align-items: center;"> <div style="background-color: red; color: white; border-radius: 50%; padding: 5px; margin-right: 10px;">NEW</div> <div> <p>EPO-Max black, epoxy resin, with high edge retention » very high hardness, easy cleaning of mould and ram due to low adhesion » with mineral filler</p> </div> </div>		
95013811	1 kg	EPO-Max black
95013812	5 kg	EPO-Max black
95013813	10 kg	EPO-Max black
<p>Epo black, epoxy resin, with high edge retention » very high hardness » contains a high proportion of glass and mineral filler</p>		
95011990	1 kg	Epo black
95011991	5 kg	Epo black
95011992	10 kg	Epo black
<p>Duroplast blue, diallylphthalate, with high edge retention » general purpose and especially for grinding stones » high hardness » contains a high proportion of glass fiber</p>		
95011999	1 kg	Duroplast blue
95012000	5 kg	Duroplast blue
95012001	10 kg	Duroplast blue
<p>Duroplast black, phenolic resin for SEM examinations and electrolytic polishing » medium hardness » conductive, contains graphite particles</p>		
95011993	1 kg	Duroplast black
95011994	5 kg	Duroplast black
95011995	10 kg	Duroplast black
<p>Thermoplast, acrylic resin for transparent mounts » ideal for targeted preparations » low - medium hardness</p>		
95011996	1 kg	Thermoplast
95011997	5 kg	Thermoplast
95011998	10 kg	Thermoplast
<p>Bakelite black, phenolic resin for general purpose » medium hardness » contains wood powder » very convenient material for filling</p>		
95011981	1 kg	Bakelite black
95011982	5 kg	Bakelite black
95011983	10 kg	Bakelite black
<p>Bakelite red, phenolic resin for general purpose » medium hardness » contains wood powder</p>		
95011984	1 kg	Bakelite red
95011985	5 kg	Bakelite red
95011986	10 kg	Bakelite red
<p>Bakelite green, phenolic resin for general purpose » medium hardness » contains wood powder</p>		
95011987	1 kg	Bakelite green
95011988	5 kg	Bakelite green
95011989	10 kg	Bakelite green





Properties of cold (castable) mounting materials

Mounting material	Recommended Application	Basis/ Filler	Hardness (Shore D)	Removal rate (grindability)
KEM 15 plus	With high edge retention, edge examination, medium-hard to hard materials	Methyl-methacrylate/ styrole	85	very low
KEM 20	Transparent mounting (pressure vessel), targeted preparation	Methyl-methacrylate	84	medium
KEM 30	Semi-transparent mounting (pressure vessel), routine work, soft to medium-hard materials	Methyl-methacrylate	85	medium
KEM 35	Minimized gap formation, edge examination, medium-hard to hard materials	Methyl-methacrylate/ ceramic	87	very low
KEM 60	Universal usage	Tetrahydrofurfuryl-2-methacrylate / filler mineral	85	low
KEM 90	Mounting using vacuum, sensitive and brittle materials	Epoxy resin	79	high

Item No.	Unit	Description
Infiltration set		
» for cold mounting and hardening using vacuum, recommended for Epoxy resin		
Z6510000	1 Pcs.	desiccator incl. non-return valve, vacuum pump, hose and pressure gauge
Infiltration unit		
» for cold mounting, pouring and hardening using vacuum		
M6500001	1 Pcs.	infiltration unit, 230 V/50 Hz, vacuum pressure 0.8 bar, W 330 x H 270 x D 300 mm (including desiccator with mechanic dosing and vacuum pump, rotating disc for 8 silicon mounting cups Ø 50 mm or 9 PTFE-mounting cups Ø 40 mm, 10 mixing cups)
110 V/60 Hz on request		
Pressure unit		
Pressure equipment for bubble free hardening of methylnmethacrylates (e.g. for Technovit 4004, KEM 20), compressed air required		
92002281	1 Pcs.	Pressure equipment, dimensions: B340 x W340 x H255 mm



Item No.	Unit	Description
Cold mounting material methacrylate		
CT = curing time		
KEM 15 plus blue, opaque		
2-component system: powder + liquid (1.5:1 [Vol.-%])		
» with high edge retention, edge examination, medium-hard to hard materials		
95012019	1 Pcs.	KEM 15 plus, SET including 1 kg powder, 500 ml liquid, 40 mixing cups, 40 mixing sticks, 2 dosing spoons
95011628	1 kg	KEM 15 plus, powder, blue, opaque, suppressed gap formation, CT: approx. 20 min
95011630	10 kg	KEM 15 plus, powder, blue, opaque, suppressed gap formation, CT: approx. 20 min
95011629	500 ml	KEM 15 plus, liquid
95011631	5 l	KEM 15 plus, liquid
KEM 20, transparent (pressure appliance)		
2-component system: powder + liquid (2:1 [Vol.-%])		
» for transparent mounting (pressure vessel), targeted preparation		
95013990	1 Pcs.	KEM 20, SET including 1 kg powder, 500 ml liquid, 40 mixing cups, 40 mixing sticks, 2 dosing spoons
95013939	1 kg	KEM 20, powder, transparent, CT: approx. 12 min
95013940	5 kg	KEM 20, powder, transparent, CT: approx. 12 min
95013941	10 kg	KEM 20, powder, transparent, CT: approx. 12 min
95013942	500 ml	KEM 20, liquid
95013943	1 l	KEM 20, liquid
KEM 30, green, transparent		
2-component system: powder + liquid (2:1 [Vol.-%])		
» for semi-transparent mounting (pressure vessel), routine work, soft to medium-hard materials		
95012021	1 Pcs.	KEM 30, SET including 1 kg powder, 500 ml liquid, 40 mixing cups, 40 mixing sticks, 2 dosing spoons
92004080	1 kg	KEM 30, powder, green, transparent, CT: approx. 5 min
92004082	5 kg	KEM 30, powder, green, transparent, CT: approx. 5 min
92004081	500 ml	KEM 30, liquid
92004083	1 l	KEM 30, liquid
92002540	2.5 l	KEM 30, liquid
KEM 35, light green, opaque, low in gaps		
2-component system: powder + liquid (1.5:1 [Vol.-%])		
» for minimized gap formation, edge examination, medium-hard to very hard materials		
95012022	1 Pcs.	KEM 35, SET including 1 kg powder, 500 ml liquid, 40 mixing cups, 40 mixing sticks, 2 dosing spoons
92002473	1 kg	KEM 35, powder, light green, opaque, CT: approx. 12 min
92002474	5 kg	KEM 35, powder, light green, opaque, CT: approx. 12 min
92002512	10 kg	KEM 35, powder, light green, opaque, CT: approx. 12 min
92002475	500 ml	KEM 35, liquid
92002476	1 l	KEM 35, liquid
92002477	2.5 l	KEM 35, liquid
» Download of Safety Data Sheets at http://www.atm-m.com/products/consumables		





Item No.	Unit	Description
Cold mounting material MMA-free		
CT = curing time		
<div style="display: flex; align-items: center;"> <div style="background-color: red; color: white; border-radius: 50%; padding: 5px; margin-right: 10px;">NEW</div> <div> <p>KEM 60, red 2-component system (MMA-free): powder + liquid (2:0,9 [weight-%]) » universal usage</p> </div> </div>		
95014004	1 Pcs.	KEM 60, SET including 1 kg powder, 500 ml liquid, 40 mixing cups, 40 mixing sticks, 2 dosing spoons
95013184	1 kg	KEM 60, powder, red, CT approx. 8 - 10 min.
95013185	5 kg	KEM 60, powder, red, CT approx. 8 - 10 min.
95013186	10 kg	KEM 60, powder, red, CT approx. 8 - 10 min.
95013187	500 ml	KEM 60, liquid
Cold mounting material epoxy resin		
CT = curing time		
<p>KEM 90, clear, transparent 2-components-system: resin + hardener (2:1 [weight-%]) » suitable for vacuum infiltration e.g. porous materials</p>		
92002484	500 ml	KEM 90, resin, clear, transparent, CT: approx. 16 - 24 h
92002485	250 ml	KEM 90, hardener
Cold mounting material methacrylate		
CT = curing time		
<p>Technovit 4000 SET white, opaque 3-component system: powder + fluid 1 + fluid 2 (3:2:1 [Vol.-%]) » with high edge retention, edge examination, medium hard to hard materials</p>		
92001683	1 Pcs.	Technovit 4000 SET (750 g / 500 ml / 250 ml), white, opaque, CT: approx. 8 min
92001684	1 Pcs.	Technovit 4000 SET (1.5 kg / 1 Ltr. / 500 ml), white, opaque, CT: approx. 8 min
<div style="background-color: yellow; padding: 2px;">Alternative: KEM 20</div> <p>Technovit 4004, transparent 2-component system: powder + liquid (2:1 [Vol.-%]) » for transparent embedding (pressure vessel), target preparation</p>		
92001688	1 kg	Technovit 4004, powder, transparent (bubble-free in pressure appliance), CT: approx. 12 min
92001689	2 kg	Technovit 4004, powder, transparent (bubble-free in pressure appliance), CT: approx. 12 min
92001691	500 ml	Technovit 4004, liquid
92001692	1 l	Technovit 4004, liquid
<div style="background-color: yellow; padding: 2px;">Alternative: KEM 30</div> <p>Technovit 4071, green, transparent 2-component system: powder + liquid (2:1 [Vol.-%]) » for semi-transparent embedding, (pressure vessel), routine embedding, medium hard to hard materials</p>		
92001695	1 kg	Technovit 4071, powder, green, transparent, CT: approx. 4-6 min
92001696	2 kg	Technovit 4071, powder, green, transparent, CT: approx. 4-6 min
92001698	500 ml	Technovit 4071, liquid
92001699	1 l	Technovit 4071, liquid
<p>Technovit 5000, copper-brown 2-component system: powder + fluid (1,55:1 [Vol.-%]) » conductive, for SEM examinations</p>		
95004058	1 kg	Technovit 5000, powder, copper-brown (bubble-free with pressure vessel), CT: approx. 7 min.
95004059	500 ml	Technovit 5000, liquid
<p>» Download of Safety Data Sheets at http://www.atm-m.com/products/consumables</p>		



Item No.	Unit	Description
Accessories for cold mounting		
Accessories for cold mounting		
92001715	100 Pcs.	Mixing cups, disposable, 180 ml
92004360	1 Pcs.	Silicon mixing cup, reusable
92001717	100 Pcs.	Mixing sticks (wood)
92002623	100 Pcs.	Plastic mounting aid Ø 30 mm, gap 1 mm
92002625	100 Pcs.	Plastic mounting aid Ø 30 mm, gap 2 mm
92002624	100 Pcs.	Plastic mounting aid Ø 30 mm, gap 3 mm
92002658	1 Pcs.	Funnel for hot mounting material
92002715	1 Pcs.	Square bottle with screw-top for approx. 1 ltr. mounting material
92002657	100 Pcs.	Angle adapter for angled polishing, 10°
92001716	10 Pcs.	Dosing spoon for hot and cold mounting material, 13 ml
92001779	10 Pcs.	Dosing spoon for cold mounting material, 20 ml
92001781	10 Pcs.	Dosing spoon for cold mounting material, 13 ml
92002662	100 Pcs.	Steel clip for for aligning thin samples in mould
92002663	100 Pcs.	Plastic clip for aligning thin samples in mould, transparent
92002707	100 Pcs.	Plastic clip for aligning thin samples in mould, black
92002708	100 Pcs.	Plastic clip for aligning thin samples in mould, red
92002709	100 Pcs.	Plastic clip for aligning thin samples in mould, grey

Cold mounting moulds

Silicon rubber round, beveled edge reusable, not suitable for light curing

92002511	1 Pcs.	Silicon rubber round, Ø 25 mm / H 23 mm
92002504	1 Pcs.	Silicon rubber round, Ø 30 mm / H 25 mm
92002505	1 Pcs.	Silicon rubber round, Ø 32 mm / H 25 mm
92002506	1 Pcs.	Silicon rubber round, Ø 38 mm / H 25 mm
92005567	1 Pcs.	Silicon rubber round, Ø 40 mm / H 30 mm
92005568	1 Pcs.	Silicon rubber round, Ø 50 mm / H 30 mm

Silicon rubber square, beveled edge reusable, not suitable for light curing

92002509	1 Pcs.	Silicon rubber square, 55 x 30 mm / H 22 mm
92002510	1 Pcs.	Silicon rubber square, 70 x 40 mm / H 22 mm

Polypropylen round reusable, for light curing, with exchangeable bottom

92001719	1 Pcs.	Polypropylen round, Ø 25 mm / H 27 mm
92001710	1 Pcs.	Polypropylen round, Ø 30 mm / H 27 mm
92001711	1 Pcs.	Polypropylen round, Ø 40 mm / H 27 mm

PTFE round, beveled edge reusable, not suitable for light curing, with exchangeable bottom

92002513	1 Pcs.	PTFE round, Ø 25 mm / H 23 mm
92002514	1 Pcs.	PTFE round, Ø 30 mm / H 25 mm
92002515	1 Pcs.	PTFE round, Ø 32 mm / H 25 mm
92002516	1 Pcs.	PTFE round, Ø 38 mm / H 25 mm
92002517	1 Pcs.	PTFE round, Ø 40 mm / H 30 mm
92002518	1 Pcs.	PTFE round, Ø 50 mm / H 30 mm
92002519	1 Pcs.	PTFE round, Ø 70 mm / H 30 mm







Grinding, Polishing, Etching

Solution Boxes / Planar grinding



Solution Boxes	28-29
Planar grinding stone for Saphir 375	30

Grinding



NEW: POLARIS SIC grinding discs	31
NEW: POLARIS M diamond grinding discs	32
NEW: POLARIS H diamond grinding discs	33
NEW: QUASAR diamond grinding discs	34
NEW: VEGA diamond grinding discs	35
GALAXY diamond grinding discs	36
NEW: GALAXY fine grinding disc Contero S	37
GALAXY fine grinding disc Contero H	37
Diamond grinding foils, metal bond	38
Zirconia aluminum oxid grinding papers for coarse grinding	38
Silicon carbide grinding foils	39
Adhere carrier discs, double-sided	40
Alumina grinding foils	40
Silicon carbide grinding paper, with foil reverse back	41-42
Silicon carbide grinding papers	42-45
Clamping rings	44
Double-sided adhesive foils	45
Grinding papers for Saphir 300 (mobile grinder and polisher)	46
Silicon carbide grinding belts	46

Polishing



Dia-COMPLETE Poly, All-In-One Diamond suspension, water-based	47
NEW: Dia-COMPLETE Poly+, All-In-One Diamond suspension, water-based	48
Dia-COMPLETE Mono, All-In-One Diamond suspension, water-based	49
NEW: Dia-COMPLETE Mono+, All-In-One Diamond suspension, water-based	50
Diamond suspension polycrystalline	51
NEW: Diamond suspension polycrystalline+	52
Diamond suspension monocrystalline	53
NEW: Diamond suspension monocrystalline+	54-55
Diamond suspension (alcohol-based) polycrystalline	56
Diamond suspension (alcohol-based) monocrystalline	56
Diamond suspension (oil-based) polycrystalline	56
Diamond suspension (oil-based) monocrystalline	56
Diamond spray polycrystalline	57
Diamond paste polycrystalline	57
Diamond paste monocrystalline	57
NEW: Diamond stick monocrystalline	57
Diamond lubricant	58
Alumina suspension, calcinated	59
Fine polishing suspensions	59
GALAXY Polishing cloths with metal back for diamond polishing	60-61
Polishing cloths, self-adhesive	62-63
Polishing cloth carrier discs	64
Carrier plate	64
Magnetic foil, self-adhesive	64

Etching



Electrolytes	65
Accessories for Kristall 650	65
Etchants	66



Item No.	Unit	Description
Solution Boxes		
Set of consumables including preparation guide for respective materials		
Solution Box Al (≥99,7%), wrought Al alloys		
95013971	1 Pcs.	Solution Box Ø 200 mm Al (≥99,7%), wrought Al alloys
95013972	1 Pcs.	Solution Box Ø 250 mm Al (≥99,7%), wrought Al alloys
95013973	1 Pcs.	Solution Box Ø 300 mm Al (≥99,7%), wrought Al alloys
Aluminum alloys		
95013900	1 Pcs.	Solution Box Ø 200 mm Aluminum alloys
95013883	1 Pcs.	Solution Box Ø 250 mm Aluminum alloys
95013473	1 Pcs.	Solution Box Ø 300 mm Aluminum alloys
Composites (CFC/GFC)		
95013911	1 Pcs.	Solution Box Ø 200 mm Composites (CFC/GFC)
95013894	1 Pcs.	Solution Box Ø 250 mm Composites (CFC/GFC)
95013877	1 Pcs.	Solution Box Ø 300 mm Composites (CFC/GFC)
Cast iron (GJS/GJL)		
95013915	1 Pcs.	Solution Box Ø 200 mm Cast iron (GJS/GJL)
95013898	1 Pcs.	Solution Box Ø 250 mm Cast iron (GJS/GJL)
95013881	1 Pcs.	Solution Box Ø 300 mm Cast iron (GJS/GJL)
Soft to medium-hard steel		
95013913	1 Pcs.	Solution Box Ø 200 mm Soft to medium-hard steel
95013896	1 Pcs.	Solution Box Ø 250 mm Soft to medium-hard steel
95013879	1 Pcs.	Solution Box Ø 300 mm Soft to medium-hard steel
Medium-hard to hard steel		
95013901	1 Pcs.	Solution Box Ø 200 mm Medium-hard to hard steel
95013884	1 Pcs.	Solution Box Ø 250 mm Medium-hard to hard steel
95013474	1 Pcs.	Solution Box Ø 300 mm Medium-hard to hard steel
Stainless steel		
95013914	1 Pcs.	Solution Box Ø 200 mm Stainless steel
95013897	1 Pcs.	Solution Box Ø 250 mm Stainless steel
95013880	1 Pcs.	Solution Box Ø 300 mm Stainless steel
Steel and welded steel (macro)		
95013910	1 Pcs.	Solution Box Ø 200 mm Steel and welded steel (macro)
95013893	1 Pcs.	Solution Box Ø 250 mm Steel and welded steel (macro)
95013876	1 Pcs.	Solution Box Ø 300 mm Steel and welded steel (macro)
Nitrided steel		
95013916	1 Pcs.	Solution Box Ø 200 mm Nitrided steel
95013899	1 Pcs.	Solution Box Ø 250 mm Nitrided steel
95013882	1 Pcs.	Solution Box Ø 300 mm Nitrided steel
Ceramics		
95013904	1 Pcs.	Solution Box Ø 200 mm Ceramics
95013887	1 Pcs.	Solution Box Ø 250 mm Ceramics
95013870	1 Pcs.	Solution Box Ø 300 mm Ceramics



Item No.	Unit	Description		
Solution Boxes				
Set of consumables including preparation guide for respective materials				
Cobalt based alloy				
95013907	1 Pcs.	Solution Box	Ø 200 mm	Cobalt based alloy
95013890	1 Pcs.	Solution Box	Ø 250 mm	Cobalt based alloy
95013873	1 Pcs.	Solution Box	Ø 300 mm	Cobalt based alloy
Nickel based alloy				
95013974	1 Pcs.	Solution Box	Ø 200 mm	Nickel based alloy
95013975	1 Pcs.	Solution Box	Ø 250 mm	Nickel based alloy
95013976	1 Pcs.	Solution Box	Ø 300 mm	Nickel based alloy
Spray coatings (metallic)				
95013906	1 Pcs.	Solution Box	Ø 200 mm	Spray coatings (metallic)
95013889	1 Pcs.	Solution Box	Ø 250 mm	Spray coatings (metallic)
95013872	1 Pcs.	Solution Box	Ø 300 mm	Spray coatings (metallic)
Magnesium based alloy				
95013912	1 Pcs.	Solution Box	Ø 200 mm	Magnesium
95013895	1 Pcs.	Solution Box	Ø 250 mm	Magnesium
95013878	1 Pcs.	Solution Box	Ø 300 mm	Magnesium
Circuit board (non assembled)				
95013903	1 Pcs.	Solution Box	Ø 200 mm	Circuit board (non assembled)
95013886	1 Pcs.	Solution Box	Ø 250 mm	Circuit board (non assembled)
95013869	1 Pcs.	Solution Box	Ø 300 mm	Circuit board (non assembled)
Circuit board (assembled)				
95013908	1 Pcs.	Solution Box	Ø 200 mm	Circuit board (assembled)
95013891	1 Pcs.	Solution Box	Ø 250 mm	Circuit board (assembled)
95013874	1 Pcs.	Solution Box	Ø 300 mm	Circuit board (assembled)
Copper and copper alloys				
95013902	1 Pcs.	Solution Box	Ø 200 mm	Copper and copper alloys
95013885	1 Pcs.	Solution Box	Ø 250 mm	Copper and copper alloys
95013475	1 Pcs.	Solution Box	Ø 300 mm	Copper and copper alloys
Titanium (grade 1-4)				
95013909	1 Pcs.	Solution Box	Ø 200 mm	Titanium (grade 1-4)
95013892	1 Pcs.	Solution Box	Ø 250 mm	Titanium (grade 1-4)
95013875	1 Pcs.	Solution Box	Ø 300 mm	Titanium (grade 1-4)
Titanium alloys				
95013905	1 Pcs.	Solution Box	Ø 200 mm	Titanium alloys
95013888	1 Pcs.	Solution Box	Ø 250 mm	Titanium alloys
95013871	1 Pcs.	Solution Box	Ø 300 mm	Titanium alloys






Item No.	Unit	Description				
Planar grinding stone for Saphir 375						
		Usable Thickness	Arbor Size	Grain Size FEPA-standard	Ø	Inner Ø
SIC grinding stone » for sintered materials (low- and unalloyed), aluminum, chilled cast iron, copper						
95002223	1 Pcs.	30 mm	40 mm	80	350 mm	90 mm
White corundum grinding stone » for tool steel (hardened and not hardened), stainless steel, steel and cast iron						
95000180	1 Pcs.	30 mm	40 mm	100	350 mm	90 mm
95000210	1 Pcs.	30 mm	40 mm	150	350 mm	90 mm
95002034	1 Pcs.	30 mm	40 mm	180	350 mm	90 mm
» inner diameter 120 mm on request						
Multi point dressing diamond » for dressing face grinding stones						
92008759	1 Pcs.	Multi point dressing diamond				

Information about grinding stones for planar grinding / practically useable grinding layer thickness

All ATM grinding stones for planar grinding have a metal back, which enlarges the practically useable grinding layer thickness of the grinding stones. Common grinding stones have a practically useable grinding layer thickness of 20 mm, whereas the ATM grinding stones have 32 mm (60% more!).



Carrier systems for grinding tools



Item No.	Unit	Description
NEW		
POLARIS SIC grinding discs		
		Description Grain Ø Fixation for soft materials, titanium materials, grinding paper applications » synthetic resin bond » long service life » incl. cleaning stone
95014996	1 Pcs.	POLARIS SIC Grinding Disc 120 µm 200 mm Adhesion carrier/Magnet carrier
95014997	1 Pcs.	POLARIS SIC Grinding Disc 220 µm 200 mm Adhesion carrier/Magnet carrier
95014998	1 Pcs.	POLARIS SIC Grinding Disc 500 µm 200 mm Adhesion carrier/Magnet carrier
95014999	1 Pcs.	POLARIS SIC Grinding Disc 800 µm 200 mm Adhesion carrier/Magnet carrier
95015000	1 Pcs.	POLARIS SIC Grinding Disc 1200 µm 200 mm Adhesion carrier/Magnet carrier
95015021	1 Pcs.	POLARIS SIC Grinding Disc 120 µm 250 mm Adhesion carrier/Magnet carrier
95015022	1 Pcs.	POLARIS SIC Grinding Disc 220 µm 250 mm Adhesion carrier/Magnet carrier
95015023	1 Pcs.	POLARIS SIC Grinding Disc 500 µm 250 mm Adhesion carrier/Magnet carrier
95015024	1 Pcs.	POLARIS SIC Grinding Disc 800 µm 250 mm Adhesion carrier/Magnet carrier
95015025	1 Pcs.	POLARIS SIC Grinding Disc 1200 µm 250 mm Adhesion carrier/Magnet carrier
95015046	1 Pcs.	POLARIS SIC Grinding Disc 120 µm 300 mm Adhesion carrier/Magnet carrier
95015047	1 Pcs.	POLARIS SIC Grinding Disc 220 µm 300 mm Adhesion carrier/Magnet carrier
95015048	1 Pcs.	POLARIS SIC Grinding Disc 500 µm 300 mm Adhesion carrier/Magnet carrier
95015049	1 Pcs.	POLARIS SIC Grinding Disc 800 µm 300 mm Adhesion carrier/Magnet carrier
95015050	1 Pcs.	POLARIS SIC Grinding Disc 1200 µm 300 mm Adhesion carrier/Magnet carrier
95015071	1 Pcs.	POLARIS SIC Grinding Disc 120 µm 350 mm Adhesion carrier/Magnet carrier
95015072	1 Pcs.	POLARIS SIC Grinding Disc 220 µm 350 mm Adhesion carrier/Magnet carrier
95015073	1 Pcs.	POLARIS SIC Grinding Disc 500 µm 350 mm Adhesion carrier/Magnet carrier
95015074	1 Pcs.	POLARIS SIC Grinding Disc 800 µm 350 mm Adhesion carrier/Magnet carrier
95015075	1 Pcs.	POLARIS SIC Grinding Disc 1200 µm 350 mm Adhesion carrier/Magnet carrier
» incl. cleaning stone No. 95015075		



Item No.	Unit	Description	Grain Size	Ø	Fixation
NEW					
POLARIS M diamond grinding discs					
Description					
for metals, ceramics, glass and plastics					
» medium-hard synthetic resin bond					
» long service life					
» incl. cleaning stone					
95014991	1 Pcs.	POLARIS M Diamond Disc	60 µm	200 mm	Adhesion carrier/Magnet carrier
95014992	1 Pcs.	POLARIS M Diamond Disc	30 µm	200 mm	Adhesion carrier/Magnet carrier
95014993	1 Pcs.	POLARIS M Diamond Disc	15 µm	200 mm	Adhesion carrier/Magnet carrier
95014994	1 Pcs.	POLARIS M Diamond Disc	6 µm	200 mm	Adhesion carrier/Magnet carrier
95014995	1 Pcs.	POLARIS M Diamond Disc	3 µm	200 mm	Adhesion carrier/Magnet carrier
95015016	1 Pcs.	POLARIS M Diamond Disc	60 µm	250 mm	Adhesion carrier/Magnet carrier
95015017	1 Pcs.	POLARIS M Diamond Disc	30 µm	250 mm	Adhesion carrier/Magnet carrier
95015018	1 Pcs.	POLARIS M Diamond Disc	15 µm	250 mm	Adhesion carrier/Magnet carrier
95015019	1 Pcs.	POLARIS M Diamond Disc	6 µm	250 mm	Adhesion carrier/Magnet carrier
95015020	1 Pcs.	POLARIS M Diamond Disc	3 µm	250 mm	Adhesion carrier/Magnet carrier
95015041	1 Pcs.	POLARIS M Diamond Disc	60 µm	300 mm	Adhesion carrier/Magnet carrier
95015042	1 Pcs.	POLARIS M Diamond Disc	30 µm	300 mm	Adhesion carrier/Magnet carrier
95015043	1 Pcs.	POLARIS M Diamond Disc	15 µm	300 mm	Adhesion carrier/Magnet carrier
95015044	1 Pcs.	POLARIS M Diamond Disc	6 µm	300 mm	Adhesion carrier/Magnet carrier
95015045	1 Pcs.	POLARIS M Diamond Disc	3 µm	300 mm	Adhesion carrier/Magnet carrier
95015066	1 Pcs.	POLARIS M Diamond Disc	60 µm	350 mm	Adhesion carrier/Magnet carrier
95015067	1 Pcs.	POLARIS M Diamond Disc	30 µm	350 mm	Adhesion carrier/Magnet carrier
95015068	1 Pcs.	POLARIS M Diamond Disc	15 µm	350 mm	Adhesion carrier/Magnet carrier
95015069	1 Pcs.	POLARIS M Diamond Disc	6 µm	350 mm	Adhesion carrier/Magnet carrier
95015070	1 Pcs.	POLARIS M Diamond Disc	3 µm	350 mm	Adhesion carrier/Magnet carrier
» incl. cleaning stone No. 95015076					



Item No.	Unit	Description
NEW		
POLARIS H diamond grinding discs		
		Description Grain Size Ø Fixation for metals, ceramics, glass and plastics » hard synthetic resin bond » long service life » incl. cleaning stone
95014985	1 Pcs.	POLARIS H Diamond Disc 125 µm 200 mm Adhesion carrier/Magnet carrier
95014986	1 Pcs.	POLARIS H Diamond Disc 60 µm 200 mm Adhesion carrier/Magnet carrier
95014987	1 Pcs.	POLARIS H Diamond Disc 30 µm 200 mm Adhesion carrier/Magnet carrier
95014988	1 Pcs.	POLARIS H Diamond Disc 15 µm 200 mm Adhesion carrier/Magnet carrier
95014989	1 Pcs.	POLARIS H Diamond Disc 6 µm 200 mm Adhesion carrier/Magnet carrier
95014990	1 Pcs.	POLARIS H Diamond Disc 3 µm 200 mm Adhesion carrier/Magnet carrier
95015010	1 Pcs.	POLARIS H Diamond Disc 125 µm 250 mm Adhesion carrier/Magnet carrier
95015011	1 Pcs.	POLARIS H Diamond Disc 60 µm 250 mm Adhesion carrier/Magnet carrier
95015012	1 Pcs.	POLARIS H Diamond Disc 30 µm 250 mm Adhesion carrier/Magnet carrier
95015013	1 Pcs.	POLARIS H Diamond Disc 15 µm 250 mm Adhesion carrier/Magnet carrier
95015014	1 Pcs.	POLARIS H Diamond Disc 6 µm 250 mm Adhesion carrier/Magnet carrier
95015015	1 Pcs.	POLARIS H Diamond Disc 3 µm 250 mm Adhesion carrier/Magnet carrier
95015035	1 Pcs.	POLARIS H Diamond Disc 125 µm 300 mm Adhesion carrier/Magnet carrier
95015036	1 Pcs.	POLARIS H Diamond Disc 60 µm 300 mm Adhesion carrier/Magnet carrier
95015037	1 Pcs.	POLARIS H Diamond Disc 30 µm 300 mm Adhesion carrier/Magnet carrier
95015038	1 Pcs.	POLARIS H Diamond Disc 15 µm 300 mm Adhesion carrier/Magnet carrier
95015039	1 Pcs.	POLARIS H Diamond Disc 6 µm 300 mm Adhesion carrier/Magnet carrier
95015040	1 Pcs.	POLARIS H Diamond Disc 3 µm 300 mm Adhesion carrier/Magnet carrier
95015060	1 Pcs.	POLARIS H Diamond Disc 125 µm 350 mm Adhesion carrier/Magnet carrier
95015061	1 Pcs.	POLARIS H Diamond Disc 60 µm 350 mm Adhesion carrier/Magnet carrier
95015062	1 Pcs.	POLARIS H Diamond Disc 30 µm 350 mm Adhesion carrier/Magnet carrier
95015063	1 Pcs.	POLARIS H Diamond Disc 15 µm 350 mm Adhesion carrier/Magnet carrier
95015064	1 Pcs.	POLARIS H Diamond Disc 6 µm 350 mm Adhesion carrier/Magnet carrier
95015065	1 Pcs.	POLARIS H Diamond Disc 3 µm 350 mm Adhesion carrier/Magnet carrier
» incl. cleaning stone No. 95015077		





Item No.	Unit	Description	Grain Size	Ø	Fixation
NEW					
QUASAR diamond grinding discs					
Description					
for hard metals and ceramics, planar and pre-grinding					
» hard epoxy resin bond					
» very long service life					
» high removal rate					
» incl. dressing stone					
95014981	1 Pcs.	QUASAR Diamond Disc	252 µm	200 mm	Adhesion carrier/Magnet carrier
95014982	1 Pcs.	QUASAR Diamond Disc	125 µm	200 mm	Adhesion carrier/Magnet carrier
95014983	1 Pcs.	QUASAR Diamond Disc	91 µm	200 mm	Adhesion carrier/Magnet carrier
95014984	1 Pcs.	QUASAR Diamond Disc	46 µm	200 mm	Adhesion carrier/Magnet carrier
95015006	1 Pcs.	QUASAR Diamond Disc	252 µm	250 mm	Adhesion carrier/Magnet carrier
95015007	1 Pcs.	QUASAR Diamond Disc	125 µm	250 mm	Adhesion carrier/Magnet carrier
95015008	1 Pcs.	QUASAR Diamond Disc	91 µm	250 mm	Adhesion carrier/Magnet carrier
95015009	1 Pcs.	QUASAR Diamond Disc	46 µm	250 mm	Adhesion carrier/Magnet carrier
95015031	1 Pcs.	QUASAR Diamond Disc	252 µm	300 mm	Adhesion carrier/Magnet carrier
95015032	1 Pcs.	QUASAR Diamond Disc	125 µm	300 mm	Adhesion carrier/Magnet carrier
95015033	1 Pcs.	QUASAR Diamond Disc	91 µm	300 mm	Adhesion carrier/Magnet carrier
95015034	1 Pcs.	QUASAR Diamond Disc	46 µm	300 mm	Adhesion carrier/Magnet carrier
95015056	1 Pcs.	QUASAR Diamond Disc	252 µm	350 mm	Adhesion carrier/Magnet carrier
95015057	1 Pcs.	QUASAR Diamond Disc	125 µm	350 mm	Adhesion carrier/Magnet carrier
95015058	1 Pcs.	QUASAR Diamond Disc	91 µm	350 mm	Adhesion carrier/Magnet carrier
95015059	1 Pcs.	QUASAR Diamond Disc	46 µm	350 mm	Adhesion carrier/Magnet carrier
» incl. dressing stone No. 95015076					



Item No.	Unit	Description																								
		NEW VEGA diamond grinding discs																								
		<table border="1"> <thead> <tr> <th>Description</th> <th>Grain Size</th> <th>Ø</th> <th>Fixation</th> </tr> </thead> <tbody> <tr> <td colspan="4">for hard iron materials and rocks</td> </tr> <tr> <td colspan="4">» nickel bond</td> </tr> <tr> <td colspan="4">» long service life</td> </tr> <tr> <td colspan="4">» high removal rate</td> </tr> <tr> <td colspan="4">» suitable for petrography</td> </tr> </tbody> </table>	Description	Grain Size	Ø	Fixation	for hard iron materials and rocks				» nickel bond				» long service life				» high removal rate				» suitable for petrography			
Description	Grain Size	Ø	Fixation																							
for hard iron materials and rocks																										
» nickel bond																										
» long service life																										
» high removal rate																										
» suitable for petrography																										
95015001	1 Pcs.	VEGA Diamond Disc 125 µm 200 mm Adhesion carrier/Magnet carrier																								
95015002	1 Pcs.	VEGA Diamond Disc 75 µm 200 mm Adhesion carrier/Magnet carrier																								
95015003	1 Pcs.	VEGA Diamond Disc 54 µm 200 mm Adhesion carrier/Magnet carrier																								
95015004	1 Pcs.	VEGA Diamond Disc 25 µm 200 mm Adhesion carrier/Magnet carrier																								
95015005	1 Pcs.	VEGA Diamond Disc 10 µm 200 mm Adhesion carrier/Magnet carrier																								
95015026	1 Pcs.	VEGA Diamond Disc 125 µm 250 mm Adhesion carrier/Magnet carrier																								
95015027	1 Pcs.	VEGA Diamond Disc 75 µm 250 mm Adhesion carrier/Magnet carrier																								
95015028	1 Pcs.	VEGA Diamond Disc 54 µm 250 mm Adhesion carrier/Magnet carrier																								
95015029	1 Pcs.	VEGA Diamond Disc 25 µm 250 mm Adhesion carrier/Magnet carrier																								
95015030	1 Pcs.	VEGA Diamond Disc 10 µm 250 mm Adhesion carrier/Magnet carrier																								
95015051	1 Pcs.	VEGA Diamond Disc 125 µm 300 mm Adhesion carrier/Magnet carrier																								
95015052	1 Pcs.	VEGA Diamond Disc 75 µm 300 mm Adhesion carrier/Magnet carrier																								
95015053	1 Pcs.	VEGA Diamond Disc 54 µm 300 mm Adhesion carrier/Magnet carrier																								
95015054	1 Pcs.	VEGA Diamond Disc 25 µm 300 mm Adhesion carrier/Magnet carrier																								
95015055	1 Pcs.	VEGA Diamond Disc 10 µm 300 mm Adhesion carrier/Magnet carrier																								





Range of GALAXY grinding and polishing systems

µm	125			46			26			15
FEPA	P80-100	P100-120	P180	P240	P320	P400	P500	P600	P800	P1000
Galaxy	GREY	RED	GREEN			BLUE		YELLOW		

Item No.	Unit	Description		
GALAXY diamond grinding discs				
		Description	Ø	Fixation
		considerably reduced grinding time compared to conventional grinding systems		
		» for medium to hard steels		
		» planar grinding: grey (P80-100) / red (P100-120)		
		» fine grinding: green (P180-320) / blue (P400-600)		
		» fine grinding: yellow (P800-1000)		
95005505	1 Pcs.	GALAXY Diamond Disc Grey	200 mm	Adhesion carrier/Magnet carrier
95005521	1 Pcs.	GALAXY Diamond Disc Red	200 mm	Adhesion carrier/Magnet carrier
95005522	1 Pcs.	GALAXY Diamond Disc Green	200 mm	Adhesion carrier/Magnet carrier
95005523	1 Pcs.	GALAXY Diamond Disc Blue	200 mm	Adhesion carrier/Magnet carrier
95005524	1 Pcs.	GALAXY Diamond Disc Yellow	200 mm	Adhesion carrier/Magnet carrier
95004279	1 Pcs.	GALAXY Diamond Disc Grey	250 mm	Adhesion carrier/Magnet carrier
95004310	1 Pcs.	GALAXY Diamond Disc Red	250 mm	Adhesion carrier/Magnet carrier
95004311	1 Pcs.	GALAXY Diamond Disc Green	250 mm	Adhesion carrier/Magnet carrier
95004312	1 Pcs.	GALAXY Diamond Disc Blue	250 mm	Adhesion carrier/Magnet carrier
95004313	1 Pcs.	GALAXY Diamond Disc Yellow	250 mm	Adhesion carrier/Magnet carrier
95004280	1 Pcs.	GALAXY Diamond Disc Grey	300 mm	Adhesion carrier/Magnet carrier
95004314	1 Pcs.	GALAXY Diamond Disc Red	300 mm	Adhesion carrier/Magnet carrier
95004315	1 Pcs.	GALAXY Diamond Disc Green	300 mm	Adhesion carrier/Magnet carrier
95004316	1 Pcs.	GALAXY Diamond Disc Blue	300 mm	Adhesion carrier/Magnet carrier
95004317	1 Pcs.	GALAXY Diamond Disc Yellow	300 mm	Adhesion carrier/Magnet carrier
95013917	1 Pcs.	GALAXY Diamond Disc Grey	350 mm	Adhesion carrier/Magnet carrier
95013918	1 Pcs.	GALAXY Diamond Disc Red	350 mm	Adhesion carrier/Magnet carrier
95013919	1 Pcs.	GALAXY Diamond Disc Green	350 mm	Adhesion carrier/Magnet carrier
95013920	1 Pcs.	GALAXY Diamond Disc Blue	350 mm	Adhesion carrier/Magnet carrier
95013921	1 Pcs.	GALAXY Diamond Disc Yellow	350 mm	Adhesion carrier/Magnet carrier
» incl. dressing stone No. 95006603				



Item No.	Unit	Description
		GALAXY fine grinding disc Contero S
		Description Ø
		» pre-polishing and fine grinding disc » for soft to medium materials » high removal rate, high edge sharpness, long service life » recommended diamond grain size 6-15 µm
95013192	1 Pcs.	GALAXY fine grinding disc Contero S 200 mm
95013194	1 Pcs.	GALAXY fine grinding disc Contero S 250 mm
95013196	1 Pcs.	GALAXY fine grinding disc Contero S 300 mm
95013922	1 Pcs.	GALAXY fine grinding disc Contero S 350 mm



GALAXY fine grinding disc Contero H		
Description		Ø
» pre-polishing and fine grinding disc » for medium to hard materials » high removal rate, high edge sharpness, long service life » recommended diamond grain size 6-15 µm		
95013193	1 Pcs.	GALAXY fine grinding disc Contero H 200 mm
95013195	1 Pcs.	GALAXY fine grinding disc Contero H 250 mm
95013197	1 Pcs.	GALAXY fine grinding disc Contero H 300 mm
95013923	1 Pcs.	GALAXY fine grinding disc Contero H 350 mm





Item No.	Unit	Description		
Diamond grinding foils, metal bond				
		Ø	Grain Size	
very long lifetime				
» for planar and fine grinding of samples with medium to very high hardness, esp. rocks, glass, ceramics, silicon				
92002289	1 Pcs.	200 mm	20 µm	self-adhesive
92002292	1 Pcs.	200 mm	40 µm	self-adhesive
92002293	1 Pcs.	200 mm	74 µm	self-adhesive
92002294	1 Pcs.	200 mm	125 µm	self-adhesive
92002301	1 Pcs.	250 mm	20 µm	self-adhesive
92002299	1 Pcs.	250 mm	40 µm	self-adhesive
92002298	1 Pcs.	250 mm	74 µm	self-adhesive
92002297	1 Pcs.	250 mm	125 µm	self-adhesive
92002296	1 Pcs.	250 mm	250 µm	self-adhesive
92002308	1 Pcs.	300 mm	20 µm	self-adhesive
92002306	1 Pcs.	300 mm	40 µm	self-adhesive
92002305	1 Pcs.	300 mm	74 µm	self-adhesive
92002304	1 Pcs.	300 mm	125 µm	self-adhesive
92002303	1 Pcs.	300 mm	250 µm	self-adhesive

Zirconia aluminum oxid grinding papers for coarse grinding				
		Ø	Grain FEPA-Standard	Fixation
very high removal rate, long lifetime				
» for planar grinding of larger sample cross sections, spectral analysis				
92002374	25 Pcs.	200 mm	P60	self-adhesive
92002375	25 Pcs.	200 mm	P120	self-adhesive
92002376	25 Pcs.	200 mm	P180	self-adhesive
92002382	25 Pcs.	250 mm	P60	self-adhesive
92002383	25 Pcs.	250 mm	P120	self-adhesive
92002384	25 Pcs.	250 mm	P180	self-adhesive
92002386	25 Pcs.	300 mm	P60	self-adhesive
92002387	25 Pcs.	300 mm	P120	self-adhesive
92002388	25 Pcs.	300 mm	P180	self-adhesive



Item No.	Unit	Description		
Silicon carbide grinding foils				
		Ø	Grain FEPA-standard	
very plane, no rolling up » multiple use, tear-resistant, approved foil thickness » fixation without clamping ring				
92008594	100 Pcs.	200 mm	P120	Adhesion carrier/Vacuum system
92008595	100 Pcs.	200 mm	P180	Adhesion carrier/Vacuum system
95007925	100 Pcs.	200 mm	P240	Adhesion carrier/Vacuum system
92008592	100 Pcs.	200 mm	P320	Adhesion carrier/Vacuum system
92008591	100 Pcs.	200 mm	P600	Adhesion carrier/Vacuum system
95000870	100 Pcs.	200 mm	P800	Adhesion carrier/Vacuum system
92008596	100 Pcs.	200 mm	P1200	Adhesion carrier/Vacuum system
95008558	100 Pcs.	200 mm	P2500	Adhesion carrier/Vacuum system
92008557	100 Pcs.	250 mm	P120	Adhesion carrier/Vacuum system
92008558	100 Pcs.	250 mm	P180	Adhesion carrier/Vacuum system
95000899	100 Pcs.	250 mm	P240	Adhesion carrier/Vacuum system
92006305	100 Pcs.	250 mm	P320	Adhesion carrier/Vacuum system
92006304	100 Pcs.	250 mm	P600	Adhesion carrier/Vacuum system
95000900	100 Pcs.	250 mm	P800	Adhesion carrier/Vacuum system
92008559	100 Pcs.	250 mm	P1200	Adhesion carrier/Vacuum system
92008639	100 Pcs.	250 mm	P2500	Adhesion carrier/Vacuum system
92008561	100 Pcs.	300 mm	P120	Adhesion carrier/Vacuum system
92008658	100 Pcs.	300 mm	P180	Adhesion carrier/Vacuum system
95000902	100 Pcs.	300 mm	P240	Adhesion carrier/Vacuum system
92006303	100 Pcs.	300 mm	P320	Adhesion carrier/Vacuum system
92006302	100 Pcs.	300 mm	P600	Adhesion carrier/Vacuum system
95000903	100 Pcs.	300 mm	P800	Adhesion carrier/Vacuum system
92008562	100 Pcs.	300 mm	P1200	Adhesion carrier/Vacuum system
92008621	100 Pcs.	300 mm	P2500	Adhesion carrier/Vacuum system
95015187	100 Pcs.	350 mm	P120	Adhesion carrier/Vacuum system
95015188	100 Pcs.	350 mm	P180	Adhesion carrier/Vacuum system
95015189	100 Pcs.	350 mm	P240	Adhesion carrier/Vacuum system
95015190	100 Pcs.	350 mm	P320	Adhesion carrier/Vacuum system
95015191	100 Pcs.	350 mm	P600	Adhesion carrier/Vacuum system
95015192	100 Pcs.	350 mm	P800	Adhesion carrier/Vacuum system
95015193	100 Pcs.	350 mm	P1200	Adhesion carrier/Vacuum system
95015194	100 Pcs.	350 mm	P2500	Adhesion carrier/Vacuum system





Item No.	Unit	Description
Adhesion carrier discs, double-sided		
Ø		
permanent adhesion on both sides, reusable		
» suitable for all fixing systems (standard, magnetic)		
» no adhesive residues		
95003781	1 Pcs.	200 mm
95003607	1 Pcs.	250 mm
95003608	1 Pcs.	300 mm
95014566	1 Pcs.	350 mm
» before initial use please remove protective foil on both sides		

Information adhesion carrier

The ATM adhere carrier is a universal adapter with nano-active surface. Consequently, a good adhesion combined with easy disassembling of the grinding and polishing discs are guaranteed.

The adhesion carrier is compatible with:

GALAXY grinding and polishing discs, SiC foils, SiC paper (with foiled back), polishing cloths with carrier disc.

Alumina grinding foils					
Ø Grain Size FEPA-standard					
» for all applications, spectral analysis					
» very plane grinding					
» multiple use					
95002894	100 Pcs.	250 mm	P120	Adhesion carrier/Vacuum system	
95002895	100 Pcs.	250 mm	P240	Adhesion carrier/Vacuum system	
95002897	100 Pcs.	250 mm	P400	Adhesion carrier/Vacuum system	
95002898	100 Pcs.	250 mm	P600	Adhesion carrier/Vacuum system	
95002903	100 Pcs.	250 mm	P800	Adhesion carrier/Vacuum system	
95002899	100 Pcs.	250 mm	P1200	Adhesion carrier/Vacuum system	
95003680	100 Pcs.	250 mm	P2500	Adhesion carrier/Vacuum system	
92008672	100 Pcs.	300 mm	P120	Adhesion carrier/Vacuum system	
92008673	100 Pcs.	300 mm	P240	Adhesion carrier/Vacuum system	
92008674	100 Pcs.	300 mm	P400	Adhesion carrier/Vacuum system	
92008675	100 Pcs.	300 mm	P600	Adhesion carrier/Vacuum system	
95003258	100 Pcs.	300 mm	P800	Adhesion carrier/Vacuum system	
92008676	100 Pcs.	300 mm	P1200	Adhesion carrier/Vacuum system	
95003259	100 Pcs.	300 mm	P2500	Adhesion carrier/Vacuum system	

Especially suitable for adhere carrier disc (page 40)



Item No.	Unit	Description		
Silicon carbide grinding paper, with foil backing				
Ø Grain FEPA-standard				
» for all adhesive systems e.g. adhesion carrier disc				
95011898	100 Pcs.	200 mm	P80	Adhesion carrier/Vacuum system
95011899	100 Pcs.	200 mm	P120	Adhesion carrier/Vacuum system
95011900	100 Pcs.	200 mm	P180	Adhesion carrier/Vacuum system
95011901	100 Pcs.	200 mm	P240	Adhesion carrier/Vacuum system
95011902	100 Pcs.	200 mm	P320	Adhesion carrier/Vacuum system
95011903	100 Pcs.	200 mm	P400	Adhesion carrier/Vacuum system
95011904	100 Pcs.	200 mm	P500	Adhesion carrier/Vacuum system
95011905	100 Pcs.	200 mm	P600	Adhesion carrier/Vacuum system
95011906	100 Pcs.	200 mm	P800	Adhesion carrier/Vacuum system
95011907	100 Pcs.	200 mm	P1000	Adhesion carrier/Vacuum system
95011908	100 Pcs.	200 mm	P1200	Adhesion carrier/Vacuum system
95011909	100 Pcs.	200 mm	P2500	Adhesion carrier/Vacuum system
95011928	100 Pcs.	250 mm	P80	Adhesion carrier/Vacuum system
95011929	100 Pcs.	250 mm	P120	Adhesion carrier/Vacuum system
95011930	100 Pcs.	250 mm	P180	Adhesion carrier/Vacuum system
95011931	100 Pcs.	250 mm	P240	Adhesion carrier/Vacuum system
95011932	100 Pcs.	250 mm	P320	Adhesion carrier/Vacuum system
95011933	100 Pcs.	250 mm	P400	Adhesion carrier/Vacuum system
95011934	100 Pcs.	250 mm	P500	Adhesion carrier/Vacuum system
95011935	100 Pcs.	250 mm	P600	Adhesion carrier/Vacuum system
95011936	100 Pcs.	250 mm	P800	Adhesion carrier/Vacuum system
95011937	100 Pcs.	250 mm	P1000	Adhesion carrier/Vacuum system
95011938	100 Pcs.	250 mm	P1200	Adhesion carrier/Vacuum system
95011939	100 Pcs.	250 mm	P2500	Adhesion carrier/Vacuum system
95011943	100 Pcs.	300 mm	P80	Adhesion carrier/Vacuum system
95011944	100 Pcs.	300 mm	P120	Adhesion carrier/Vacuum system
95011945	100 Pcs.	300 mm	P180	Adhesion carrier/Vacuum system
95011946	100 Pcs.	300 mm	P240	Adhesion carrier/Vacuum system
95011947	100 Pcs.	300 mm	P320	Adhesion carrier/Vacuum system
95011948	100 Pcs.	300 mm	P400	Adhesion carrier/Vacuum system
95011949	100 Pcs.	300 mm	P500	Adhesion carrier/Vacuum system
95011950	100 Pcs.	300 mm	P600	Adhesion carrier/Vacuum system
95011951	100 Pcs.	300 mm	P800	Adhesion carrier/Vacuum system
95011952	100 Pcs.	300 mm	P1000	Adhesion carrier/Vacuum system
95011953	100 Pcs.	300 mm	P1200	Adhesion carrier/Vacuum system
95011954	100 Pcs.	300 mm	P2500	Adhesion carrier/Vacuum system

Especially suitable for adhere carrier disc (page 40)





Item No.	Unit	Description		
Silicon carbide grinding paper, with foil backing				
Ø Grain FEPA-standard				
» for all adhesive systems e.g. adhesion carrier disc				
95014005	100 Pcs.	350 mm	P80	Adhesion carrier/Vacuum system
95014006	100 Pcs.	350 mm	P120	Adhesion carrier/Vacuum system
95014007	100 Pcs.	350 mm	P180	Adhesion carrier/Vacuum system
95014008	100 Pcs.	350 mm	P240	Adhesion carrier/Vacuum system
95014009	100 Pcs.	350 mm	P320	Adhesion carrier/Vacuum system
95014010	100 Pcs.	350 mm	P400	Adhesion carrier/Vacuum system
95014011	100 Pcs.	350 mm	P500	Adhesion carrier/Vacuum system
95014012	100 Pcs.	350 mm	P600	Adhesion carrier/Vacuum system
95014013	100 Pcs.	350 mm	P800	Adhesion carrier/Vacuum system
95014014	100 Pcs.	350 mm	P1000	Adhesion carrier/Vacuum system
95014015	100 Pcs.	350 mm	P1200	Adhesion carrier/Vacuum system
95014016	100 Pcs.	350 mm	P2500	Adhesion carrier/Vacuum system

Especially suitable for adhere carrier disc (page 40)

Silicon carbide grinding papers				
Ø	Grain FEPA-Standard	Fixation		
» for all kinds of conventional surfaces				
92002544	100 Pcs.	200 mm	P80	self-adhesive
92002545	100 Pcs.	200 mm	P120	self-adhesive
92002546	100 Pcs.	200 mm	P180	self-adhesive
92002547	100 Pcs.	200 mm	P240	self-adhesive
92002548	100 Pcs.	200 mm	P320	self-adhesive
92002549	100 Pcs.	200 mm	P400	self-adhesive
92004516	100 Pcs.	200 mm	P600	self-adhesive
92002550	100 Pcs.	200 mm	P800	self-adhesive
92002551	100 Pcs.	200 mm	P1000	self-adhesive
92002638	100 Pcs.	200 mm	P1200	self-adhesive
92002761	100 Pcs.	200 mm	P2400	self-adhesive
92004561	100 Pcs.	200 mm	P2500	self-adhesive
92002762	100 Pcs.	200 mm	P4000	self-adhesive



Item No.	Unit	Description		
Silicon carbide grinding papers				
		Ø	Grain FEPA-Standard	Fixation
» for all kinds of conventional surfaces				
92001633	100 Pcs.	230 mm	P80	self-adhesive
92001634	100 Pcs.	230 mm	P120	self-adhesive
92001635	100 Pcs.	230 mm	P180	self-adhesive
92001636	100 Pcs.	230 mm	P240	self-adhesive
92001637	100 Pcs.	230 mm	P320	self-adhesive
92001638	100 Pcs.	230 mm	P400	self-adhesive
92004517	100 Pcs.	230 mm	P600	self-adhesive
92001639	100 Pcs.	230 mm	P800	self-adhesive
92001640	100 Pcs.	230 mm	P1000	self-adhesive
92001641	100 Pcs.	230 mm	P1200	self-adhesive
92002862	100 Pcs.	230 mm	P2400	self-adhesive
92004562	100 Pcs.	230 mm	P2500	self-adhesive
92002863	100 Pcs.	230 mm	P4000	self-adhesive
92001643	100 Pcs.	250 mm	P80	self-adhesive
92001644	100 Pcs.	250 mm	P120	self-adhesive
92001645	100 Pcs.	250 mm	P180	self-adhesive
92004953	100 Pcs.	250 mm	P240	self-adhesive
92001647	100 Pcs.	250 mm	P320	self-adhesive
92001648	100 Pcs.	250 mm	P400	self-adhesive
92001649	100 Pcs.	250 mm	P600	self-adhesive
92001650	100 Pcs.	250 mm	P800	self-adhesive
92001651	100 Pcs.	250 mm	P1000	self-adhesive
92001652	100 Pcs.	250 mm	P1200	self-adhesive
92002763	100 Pcs.	250 mm	P2400	self-adhesive
92004563	100 Pcs.	250 mm	P2500	self-adhesive
92002764	100 Pcs.	250 mm	P4000	self-adhesive
92001654	100 Pcs.	300 mm	P80	self-adhesive
92001655	100 Pcs.	300 mm	P120	self-adhesive
92001657	100 Pcs.	300 mm	P180	self-adhesive
92001658	100 Pcs.	300 mm	P240	self-adhesive
92001659	100 Pcs.	300 mm	P320	self-adhesive
92001660	100 Pcs.	300 mm	P400	self-adhesive
92001661	100 Pcs.	300 mm	P600	self-adhesive
92001662	100 Pcs.	300 mm	P800	self-adhesive
92001663	100 Pcs.	300 mm	P1000	self-adhesive
92001664	100 Pcs.	300 mm	P1200	self-adhesive
92002765	100 Pcs.	300 mm	P2400	self-adhesive
92004564	100 Pcs.	300 mm	P2500	self-adhesive
92002766	100 Pcs.	300 mm	P4000	self-adhesive





Item No.	Unit	Description		
Silicon carbide grinding papers				
		Ø	Grain FEPA-Standard	Fixation
» without adhesive backing				
» suitable with clamping ring, adhesive foil or spray glue				
92001810	100 Pcs.	200 mm	P60	Clamping Ring/Adhesive Foil
92001811	100 Pcs.	200 mm	P80	Clamping Ring/Adhesive Foil
92001812	100 Pcs.	200 mm	P120	Clamping Ring/Adhesive Foil
92001813	100 Pcs.	200 mm	P180	Clamping Ring/Adhesive Foil
92001814	100 Pcs.	200 mm	P240	Clamping Ring/Adhesive Foil
92001815	100 Pcs.	200 mm	P320	Clamping Ring/Adhesive Foil
92001816	100 Pcs.	200 mm	P400	Clamping Ring/Adhesive Foil
92001817	100 Pcs.	200 mm	P500	Clamping Ring/Adhesive Foil
92001818	100 Pcs.	200 mm	P600	Clamping Ring/Adhesive Foil
92001819	100 Pcs.	200 mm	P800	Clamping Ring/Adhesive Foil
92001820	100 Pcs.	200 mm	P1000	Clamping Ring/Adhesive Foil
92001821	100 Pcs.	200 mm	P1200	Clamping Ring/Adhesive Foil
92002634	100 Pcs.	200 mm	P2400	Clamping Ring/Adhesive Foil
92004557	100 Pcs.	200 mm	P2500	Clamping Ring/Adhesive Foil
92002640	100 Pcs.	200 mm	P4000	Clamping Ring/Adhesive Foil
92001567	100 Pcs.	230 mm	P60	Clamping Ring/Adhesive Foil
92001568	100 Pcs.	230 mm	P80	Clamping Ring/Adhesive Foil
92001569	100 Pcs.	230 mm	P120	Clamping Ring/Adhesive Foil
92001570	100 Pcs.	230 mm	P180	Clamping Ring/Adhesive Foil
92001571	100 Pcs.	230 mm	P240	Clamping Ring/Adhesive Foil
92001572	100 Pcs.	230 mm	P320	Clamping Ring/Adhesive Foil
92001573	100 Pcs.	230 mm	P400	Clamping Ring/Adhesive Foil
92001574	100 Pcs.	230 mm	P500	Clamping Ring/Adhesive Foil
92001575	100 Pcs.	230 mm	P600	Clamping Ring/Adhesive Foil
92001576	100 Pcs.	230 mm	P800	Clamping Ring/Adhesive Foil
92001577	100 Pcs.	230 mm	P1000	Clamping Ring/Adhesive Foil
92001578	100 Pcs.	230 mm	P1200	Clamping Ring/Adhesive Foil
92002635	100 Pcs.	230 mm	P2400	Clamping Ring/Adhesive Foil
92004558	100 Pcs.	230 mm	P2500	Clamping Ring/Adhesive Foil
92001579	100 Pcs.	230 mm	P4000	Clamping Ring/Adhesive Foil

Clamping Ring

Ø

» made from plastic

05610228	1 Pcs.	200 mm
05610227	1 Pcs.	230 mm
05610226	1 Pcs.	250 mm
05610225	1 Pcs.	300 mm




Item No.	Unit	Description		
Silicon carbide grinding papers				
		Ø	Grain FEPA-Standard	Fixation
» without adhesive backing				
» suitable with clamping ring, adhesive foil or spray glue				
92001580	100 Pcs.	250 mm	P60	Clamping Ring/Adhesive Foil
92001581	100 Pcs.	250 mm	P80	Clamping Ring/Adhesive Foil
92001582	100 Pcs.	250 mm	P120	Clamping Ring/Adhesive Foil
92001583	100 Pcs.	250 mm	P180	Clamping Ring/Adhesive Foil
92002369	100 Pcs.	250 mm	P240	Clamping Ring/Adhesive Foil
92001585	100 Pcs.	250 mm	P320	Clamping Ring/Adhesive Foil
92001586	100 Pcs.	250 mm	P400	Clamping Ring/Adhesive Foil
92001587	100 Pcs.	250 mm	P500	Clamping Ring/Adhesive Foil
92001588	100 Pcs.	250 mm	P600	Clamping Ring/Adhesive Foil
92001589	100 Pcs.	250 mm	P800	Clamping Ring/Adhesive Foil
92001590	100 Pcs.	250 mm	P1000	Clamping Ring/Adhesive Foil
92001591	100 Pcs.	250 mm	P1200	Clamping Ring/Adhesive Foil
92002636	100 Pcs.	250 mm	P2400	Clamping Ring/Adhesive Foil
92004559	100 Pcs.	250 mm	P2500	Clamping Ring/Adhesive Foil
92001592	100 Pcs.	250 mm	P4000	Clamping Ring/Adhesive Foil
92001593	100 Pcs.	300 mm	P60	Clamping Ring/Adhesive Foil
92001594	100 Pcs.	300 mm	P80	Clamping Ring/Adhesive Foil
92001595	100 Pcs.	300 mm	P120	Clamping Ring/Adhesive Foil
92001596	100 Pcs.	300 mm	P180	Clamping Ring/Adhesive Foil
92001597	100 Pcs.	300 mm	P240	Clamping Ring/Adhesive Foil
92001598	100 Pcs.	300 mm	P320	Clamping Ring/Adhesive Foil
92001599	100 Pcs.	300 mm	P400	Clamping Ring/Adhesive Foil
92001600	100 Pcs.	300 mm	P500	Clamping Ring/Adhesive Foil
92001601	100 Pcs.	300 mm	P600	Clamping Ring/Adhesive Foil
92001602	100 Pcs.	300 mm	P800	Clamping Ring/Adhesive Foil
92001603	100 Pcs.	300 mm	P1000	Clamping Ring/Adhesive Foil
92001604	100 Pcs.	300 mm	P1200	Clamping Ring/Adhesive Foil
92002637	100 Pcs.	300 mm	P2400	Clamping Ring/Adhesive Foil
92004560	100 Pcs.	300 mm	P2500	Clamping Ring/Adhesive Foil
92002154	100 Pcs.	300 mm	P4000	Clamping Ring/Adhesive Foil

Double-sided adhesive foils

Ø

» for grinding papers

92002522	5 Pcs.	200 mm
92002524	5 Pcs.	250 mm
92002525	5 Pcs.	300 mm





Item No.	Unit	Description	
Grinding papers for mobile grinder and polisher			
Ø Grain FEPA-Standard			
Corundum grinding papers with hook-and-loop fastener backing			
92004285	100 Pcs.	30 mm	P60
92004286	100 Pcs.	30 mm	P180
92004288	100 Pcs.	30 mm	P240
92004287	100 Pcs.	30 mm	P320
Silicon grinding papers with adhesive backing			
92004498	100 Pcs.	30 mm	P400
92004499	100 Pcs.	30 mm	P600
92004631	100 Pcs.	30 mm	P1000
» all polishing cloths also available with Ø 30 mm			

Silicon carbide grinding belts			
Dimensions Grain FEPA-standard			
Corundum grinding belts, water resistant			
92002528	5 Pcs.	100 x 920 mm	P80
92002529	5 Pcs.	100 x 920 mm	P120
92002530	5 Pcs.	100 x 920 mm	P180
92002531	5 Pcs.	100 x 920 mm	P240
92004505	5 Pcs.	100 x 920 mm	P320
92002953	5 Pcs.	100 x 915 mm	P80
92002954	5 Pcs.	100 x 915 mm	P120
Silicon carbide grinding belts, water-resistant			
92002664	5 Pcs.	100 x 915 mm	P80
92002665	5 Pcs.	100 x 915 mm	P120
92002666	5 Pcs.	100 x 915 mm	P180
92002667	5 Pcs.	100 x 915 mm	P240
92004613	5 Pcs.	100 x 915 mm	P320
92002394	5 Pcs.	100 x 915 mm	P400



Item No.	Unit	Description	
Dia-COMPLETE Poly, All-In-One Diamond suspension, water-based			
		Grain Size (µm)	Grain Type
Combined product of diamond suspension including lubricant » water-based (ecologically friendly) » closely tolerated grain size » high diamond concentration » very high stock removal rate and repeatable results			
95016022	250 ml	0.25	polycrystalline
95011833	500 ml	0.25	polycrystalline
95011839	1 l	0.25	polycrystalline
95011845	2.5 l	0.25	polycrystalline
95016023	5 l	0.25	polycrystalline
95016024	10 l	0.25	polycrystalline
95015208	250 ml	1	polycrystalline
95011834	500 ml	1	polycrystalline
95011840	1 l	1	polycrystalline
95011846	2.5 l	1	polycrystalline
95015394	5 l	1	polycrystalline
95015399	10 l	1	polycrystalline
95015209	250 ml	3	polycrystalline
95011835	500 ml	3	polycrystalline
95011841	1 l	3	polycrystalline
95011847	2.5 l	3	polycrystalline
95015395	5 l	3	polycrystalline
95015400	10 l	3	polycrystalline
95015210	250 ml	6	polycrystalline
95011836	500 ml	6	polycrystalline
95011842	1 l	6	polycrystalline
95011848	2.5 l	6	polycrystalline
95015396	5 l	6	polycrystalline
95015401	10 l	6	polycrystalline
95015211	250 ml	9	polycrystalline
95011837	500 ml	9	polycrystalline
95011843	1 l	9	polycrystalline
95011849	2.5 l	9	polycrystalline
95015397	5 l	9	polycrystalline
95015402	10 l	9	polycrystalline
95015212	250 ml	15	polycrystalline
95011838	500 ml	15	polycrystalline
95011844	1 l	15	polycrystalline
95011850	2.5 l	15	polycrystalline
95015398	5 l	15	polycrystalline
95015403	10 l	15	polycrystalline





Item No.	Unit	Description	
		NEW	
		Dia-COMPLETE Poly+, All-In-One Diamond suspension, water-based	
		Grain Size (µm)	Grain Type
		Combined product of diamond suspension including lubricant	
		» water-based (ecologically friendly)	
		» closely tolerated grain size	
		» very high diamond concentration	
		» very high stock removal rate and repeatable results	
95015302	250 ml	0.1	polycrystalline
95015303	500 ml	0.1	polycrystalline
95015304	1 l	0.1	polycrystalline
95015305	2.5 l	0.1	polycrystalline
95015306	5 l	0.1	polycrystalline
95015307	10 l	0.1	polycrystalline
95015308	250 ml	0.25	polycrystalline
95015309	500 ml	0.25	polycrystalline
95015310	1 l	0.25	polycrystalline
95015311	2.5 l	0.25	polycrystalline
95015312	5 l	0.25	polycrystalline
95015313	10 l	0.25	polycrystalline
95015314	250 ml	1	polycrystalline
95015315	500 ml	1	polycrystalline
95015316	1 l	1	polycrystalline
95015317	2.5 l	1	polycrystalline
95015318	5 l	1	polycrystalline
95015319	10 l	1	polycrystalline
95015320	250 ml	3	polycrystalline
95015321	500 ml	3	polycrystalline
95015322	1 l	3	polycrystalline
95015323	2.5 l	3	polycrystalline
95015324	5 l	3	polycrystalline
95015325	10 l	3	polycrystalline
95015326	250 ml	6	polycrystalline
95015327	500 ml	6	polycrystalline
95015328	1 l	6	polycrystalline
95015329	2.5 l	6	polycrystalline
95015330	5 l	6	polycrystalline
95015331	10 l	6	polycrystalline
95015332	250 ml	9	polycrystalline
95015333	500 ml	9	polycrystalline
95015334	1 l	9	polycrystalline
95015335	2.5 l	9	polycrystalline
95015336	5 l	9	polycrystalline
95015337	10 l	9	polycrystalline
95015338	250 ml	15	polycrystalline
95015339	500 ml	15	polycrystalline
95015340	1 l	15	polycrystalline
95015341	2.5 l	15	polycrystalline
95015342	5 l	15	polycrystalline
95015343	10 l	15	polycrystalline




Item No.	Unit	Description	
Dia-COMplete Mono, All-In-One Diamond suspension, water-based			
		Grain Size (µm)	Grain Type
Combined product of diamond suspension including lubricant » water-based (ecologically friendly) » closely tolerated grain size » high diamond concentration » very high stock removal rate and repeatable results			
95015213	250 ml	1	monocrystalline
95011815	500 ml	1	monocrystalline
95011820	1 l	1	monocrystalline
95011825	2.5 l	1	monocrystalline
95015404	5 l	1	monocrystalline
95015409	10 l	1	monocrystalline
95015214	250 ml	3	monocrystalline
95011816	500 ml	3	monocrystalline
95011821	1 l	3	monocrystalline
95011826	2.5 l	3	monocrystalline
95015405	5 l	3	monocrystalline
95015410	10 l	3	monocrystalline
95015215	250 ml	6	monocrystalline
95011817	500 ml	6	monocrystalline
95011822	1 l	6	monocrystalline
95011827	2.5 l	6	monocrystalline
95015406	5 l	6	monocrystalline
95015411	10 l	6	monocrystalline
95015216	250 ml	9	monocrystalline
95011818	500 ml	9	monocrystalline
95011823	1 l	9	monocrystalline
95011828	2.5 l	9	monocrystalline
95015407	5 l	9	monocrystalline
95015412	10 l	9	monocrystalline
95015217	250 ml	15	monocrystalline
95011819	500 ml	15	monocrystalline
95011824	1 l	15	monocrystalline
95011829	2.5 l	15	monocrystalline
95015408	5 l	15	monocrystalline
95015413	10 l	15	monocrystalline

» Download of Safety Data Sheets at
<http://www.atm-m.com/products/consumables>





Item No.	Unit	Description	
		 Dia-COMPLETE Mono+, All-In-One Diamond suspension, water-based	
		Grain Size (µm)	Grain Type
		Combined product of diamond suspension including lubricant » water-based (ecologically friendly) » closely tolerated grain size » very high diamond concentration » very high stock removal rate and repeatable results	
95015344	250 ml	0.1	monocrystalline
95015345	500 ml	0.1	monocrystalline
95015346	1 l	0.1	monocrystalline
95015347	2.5 l	0.1	monocrystalline
95015348	5 l	0.1	monocrystalline
95015349	10 l	0.1	monocrystalline
95015350	250 ml	0.25	monocrystalline
95015351	500 ml	0.25	monocrystalline
95015352	1 l	0.25	monocrystalline
95015353	2.5 l	0.25	monocrystalline
95015354	5 l	0.25	monocrystalline
95015355	10 l	0.25	monocrystalline
95015356	250 ml	1	monocrystalline
95015357	500 ml	1	monocrystalline
95015358	1 l	1	monocrystalline
95015359	2.5 l	1	monocrystalline
95015360	5 l	1	monocrystalline
95015361	10 l	1	monocrystalline
95015362	250 ml	3	monocrystalline
95015363	500 ml	3	monocrystalline
95015364	1 l	3	monocrystalline
95015365	2.5 l	3	monocrystalline
95015366	5 l	3	monocrystalline
95015367	10 l	3	monocrystalline
95015368	250 ml	6	monocrystalline
95015369	500 ml	6	monocrystalline
95015370	1 l	6	monocrystalline
95015371	2.5 l	6	monocrystalline
95015372	5 l	6	monocrystalline
95015373	10 l	6	monocrystalline
95015374	250 ml	9	monocrystalline
95015375	500 ml	9	monocrystalline
95015376	1 l	9	monocrystalline
95015377	2.5 l	9	monocrystalline
95015378	5 l	9	monocrystalline
95015379	10 l	9	monocrystalline
95015380	250 ml	15	monocrystalline
95015381	500 ml	15	monocrystalline
95015382	1 l	15	monocrystalline
95015383	2.5 l	15	monocrystalline
95015384	5 l	15	monocrystalline
95015385	10 l	15	monocrystalline



Item No.	Unit	Description	
Diamond suspension polycrystalline			
		Grain Size (µm)	Grain Type
» water-based (ecologically friendly) » closely tolerated grain size » high diamond concentration » very high stock removal			
92002353	250 ml	1	polycrystalline
95016017	500 ml	1	polycrystalline
92004798	1 l	1	polycrystalline
95002761	2.5 l	1	polycrystalline
95014519	5 l	1	polycrystalline
95015196	10 l	1	polycrystalline
92002354	250 ml	3	polycrystalline
95016018	500 ml	3	polycrystalline
92004799	1 l	3	polycrystalline
95002762	2.5 l	3	polycrystalline
95014520	5 l	3	polycrystalline
95015199	10 l	3	polycrystalline
92002355	250 ml	6	polycrystalline
95016019	500 ml	6	polycrystalline
92004800	1 l	6	polycrystalline
95002763	2.5 l	6	polycrystalline
95014521	5 l	6	polycrystalline
95015200	10 l	6	polycrystalline
92002356	250 ml	9	polycrystalline
95016020	500 ml	9	polycrystalline
92004801	1 l	9	polycrystalline
95002764	2.5 l	9	polycrystalline
95014522	5 l	9	polycrystalline
95015201	10 l	9	polycrystalline
92002357	250 ml	15	polycrystalline
95016021	500 ml	15	polycrystalline
95005738	1 l	15	polycrystalline
95002765	2.5 l	15	polycrystalline
95014523	5 l	15	polycrystalline
95015202	10 l	15	polycrystalline
» Download of Safety Data Sheets at http://www.atm-m.com/products/consumables			





Item No.	Unit	Description	
		Diamond suspension polycrystalline+	
		Grain Size (µm)	Grain Type
		<div style="display: flex; align-items: center;"> <div style="background-color: red; color: white; border-radius: 50%; padding: 2px 5px; margin-right: 5px;">NEW</div> <ul style="list-style-type: none"> » water-based (ecologically friendly) » closely tolerated grain size » very high diamond concentration » very high stock removal </div>	
95015218	250 ml	0.1	polycrystalline
95015219	500 ml	0.1	polycrystalline
95015220	1 l	0.1	polycrystalline
95015221	2.5 l	0.1	polycrystalline
95015222	5 l	0.1	polycrystalline
95015223	10 l	0.1	polycrystalline
95015224	250 ml	0.25	polycrystalline
95015225	500 ml	0.25	polycrystalline
95015226	1 l	0.25	polycrystalline
95015227	2.5 l	0.25	polycrystalline
95015228	5 l	0.25	polycrystalline
95015229	10 l	0.25	polycrystalline
95015230	250 ml	1	polycrystalline
95015231	500 ml	1	polycrystalline
95015232	1 l	1	polycrystalline
95015233	2.5 l	1	polycrystalline
95015234	5 l	1	polycrystalline
95015235	10 l	1	polycrystalline
95015236	250 ml	3	polycrystalline
95015237	500 ml	3	polycrystalline
95015238	1 l	3	polycrystalline
95015239	2.5 l	3	polycrystalline
95015240	5 l	3	polycrystalline
95015241	10 l	3	polycrystalline
95015242	250 ml	6	polycrystalline
95015243	500 ml	6	polycrystalline
95015244	1 l	6	polycrystalline
95015245	2.5 l	6	polycrystalline
95015246	5 l	6	polycrystalline
95015247	10 l	6	polycrystalline
95015248	250 ml	9	polycrystalline
95015249	500 ml	9	polycrystalline
95015250	1 l	9	polycrystalline
95015251	2.5 l	9	polycrystalline
95015252	5 l	9	polycrystalline
95015253	10 l	9	polycrystalline
95015254	250 ml	15	polycrystalline
95015255	500 ml	15	polycrystalline
95015256	1 l	15	polycrystalline
95015257	2.5 l	15	polycrystalline
95015258	5 l	15	polycrystalline
95015259	10 l	15	polycrystalline



Item No.	Unit	Description	
Diamond suspension monocrystalline			
		Grain Size (µm)	Grain Type
» water-based (ecologically friendly) » closely tolerated grain size » high diamond concentration » very high stock removal rate			
92002346	250 ml	1	monocrystalline
95016012	500 ml	1	monocrystalline
92004791	1 l	1	monocrystalline
95002755	2.5 l	1	monocrystalline
95014514	5 l	1	monocrystalline
95015203	10 l	1	monocrystalline
92002347	250 ml	3	monocrystalline
95016013	500 ml	3	monocrystalline
92004792	1 l	3	monocrystalline
95002756	2.5 l	3	monocrystalline
95014515	5 l	3	monocrystalline
95015204	10 l	3	monocrystalline
92002348	250 ml	6	monocrystalline
95016014	500 ml	6	monocrystalline
92004793	1 l	6	monocrystalline
95002757	2.5 l	6	monocrystalline
95014516	5 l	6	monocrystalline
95015205	10 l	6	monocrystalline
92002349	250 ml	9	monocrystalline
95016015	500 ml	9	monocrystalline
92004794	1 l	9	monocrystalline
95002758	2.5 l	9	monocrystalline
95014517	5 l	9	monocrystalline
95015206	10 l	9	monocrystalline
92002350	250 ml	15	monocrystalline
95016016	500 ml	15	monocrystalline
92004795	1 l	15	monocrystalline
95002759	2.5 l	15	monocrystalline
95014518	5 l	15	monocrystalline
95015207	10 l	15	monocrystalline

» Download of Safety Data Sheets at
<http://www.atm-m.com/products/consumables>

Color code diamond suspension monocrystalline

Grain size µm	Color
1 µm	Blue
3 µm	Green
6 µm	Yellow
9 µm	Red
15 µm	Red brown





Item No.	Unit	Description	
		NEW	
		Diamond suspension monocrystalline+	
		Grain Size (µm)	Grain Type
		<ul style="list-style-type: none"> » water-based (ecologically friendly) » closely tolerated grain size » high diamond concentration » very high stock removal rate 	
95015260	250 ml	0.1	monocrystalline
95015261	500 ml	0.1	monocrystalline
95015262	1 l	0.1	monocrystalline
95015263	2.5 l	0.1	monocrystalline
95015264	5 l	0.1	monocrystalline
95015265	10 l	0.1	monocrystalline
95015266	250 ml	0.25	monocrystalline
95015267	500 ml	0.25	monocrystalline
95015268	1 l	0.25	monocrystalline
95015269	2.5 l	0.25	monocrystalline
95015270	5 l	0.25	monocrystalline
95015271	10 l	0.25	monocrystalline
95015272	250 ml	1	monocrystalline
95015273	500 ml	1	monocrystalline
95015274	1 l	1	monocrystalline
95015275	2.5 l	1	monocrystalline
95015276	5 l	1	monocrystalline
95015277	10 l	1	monocrystalline
95015278	250 ml	3	monocrystalline
95015279	500 ml	3	monocrystalline
95015280	1 l	3	monocrystalline
95015281	2.5 l	3	monocrystalline
95015282	5 l	3	monocrystalline
95015283	10 l	3	monocrystalline



Item No.	Unit	Description
		Diamond suspension monocrystalline+
		Grain Size (µm) Grain Type
		» water-based (ecologically friendly)
		» closely tolerated grain size
		» high diamond concentration
		» very high stock removal rate
95015284	250 ml	6 monocrystalline
95015285	500 ml	6 monocrystalline
95015286	1 l	6 monocrystalline
95015287	2.5 l	6 monocrystalline
95015288	5 l	6 monocrystalline
95015289	10 l	6 monocrystalline
95015290	250 ml	9 monocrystalline
95015291	500 ml	9 monocrystalline
95015292	1 l	9 monocrystalline
95015293	2.5 l	9 monocrystalline
95015294	5 l	9 monocrystalline
95015295	10 l	9 monocrystalline
95015296	250 ml	15 monocrystalline
95015297	500 ml	15 monocrystalline
95015298	1 l	15 monocrystalline
95015299	2.5 l	15 monocrystalline
95015300	5 l	15 monocrystalline
95015301	10 l	15 monocrystalline





Item No.	Unit	Description	
Diamond suspension (alcohol-based) polycrystalline			
		Grain Size (µm)	Grain Type
alcohol-based (ecologically friendly)			
» closely tolerated grain size, high diamond concentration			
» very high stock removal rate			
95003494	1 l	1	polycrystalline
95003495	1 l	3	polycrystalline
95003496	1 l	6	polycrystalline
95003497	1 l	9	polycrystalline
95007978	1 l	15	polycrystalline

Diamond suspension (alcohol-based) monocrystalline			
		Grain Size (µm)	Grain Type
alcohol-based (ecologically friendly)			
» closely tolerated grain size, high diamond concentration			
» high stock removal rate			
95003490	1 l	1	monocrystalline
95003491	1 l	3	monocrystalline
95003492	1 l	6	monocrystalline
95003493	1 l	9	monocrystalline
95007977	1 l	15	monocrystalline

Diamond suspension (oil-based) polycrystalline			
		Grain Size (µm)	Grain Type
oil-based			
» closely tolerated grain size, high diamond concentration			
» very high stock removal rate			
95002792	1 l	1	polycrystalline
95002793	1 l	3	polycrystalline
95002794	1 l	6	polycrystalline
95002795	1 l	9	polycrystalline
95002976	1 l	15	polycrystalline

Diamond suspension (oil-based) monocrystalline			
		Grain Size (µm)	Grain Type
oil-based			
» closely tolerated grain size, high diamond concentration			
» high stock removal rate			
95002767	1 l	1	monocrystalline
95002768	1 l	3	monocrystalline
95002769	1 l	6	monocrystalline
95002770	1 l	9	monocrystalline
95002771	1 l	15	monocrystalline



Item No.	Unit	Description	
Diamond spray polycrystalline			
		Grain Size (µm)	Grain Type
CFC-free » very high diamond concentration » closely tolerated grain size » very high stock removal rate			
95016025	200 ml	1	polycrystalline
95016026	200 ml	3	polycrystalline
95016027	200 ml	6	polycrystalline
95016028	200 ml	9	polycrystalline

Diamond paste polycrystalline			
		Grain Size (µm)	Grain Type
Diamond paste, 10 g syringe » closely tolerated grain size » very high diamond concentration » very high stock removal rate			
92002340	10 g	1	polycrystalline
92002341	10 g	3	polycrystalline
92002342	10 g	6	polycrystalline
92002343	10 g	9	polycrystalline
92002344	10 g	15	polycrystalline

Diamond paste monocrystalline			
		Grain Size (µm)	Grain Type
Diamond paste, 10 g syringe » closely tolerated grain size » very high diamond concentration » high stock removal rate			
92002333	10 g	1	monocrystalline
92002316	10 g	3	monocrystalline
92002335	10 g	6	monocrystalline
92002336	10 g	9	monocrystalline
92002337	10 g	15	monocrystalline



Diamond stick monocrystalline			
		Grain Size (µm)	Grain Type
» Diamond wax » to be used with lubricant » closely tolerated grain size » high diamond concentration			
95015386	10 g	1	monocrystalline
95015387	10 g	3	monocrystalline
95015388	10 g	6	monocrystalline
95015389	10 g	9	monocrystalline
95015390	10 g	15	monocrystalline

» Download of Safety Data Sheets at
<http://www.atm-m.com/products/consumables>





Item No.	Unit	Description		
Diamond lubricant				
		Color	Characteristics	
additive for diamond suspension/paste				
92005509	1 l	Yellow	- water-based -	ecologically friendly
92004925	2.5 l	Yellow	- water-based -	ecologically friendly
92005510	5 l	Yellow	- water-based -	ecologically friendly
95000901	1 l	Dark blue	- alcohol-based -	for water-free preparation
95000911	2.5 l	Dark blue	- alcohol-based -	for water-free preparation
95001194	5 l	Dark blue	- alcohol-based -	for water-free preparation
95015391	1 l	Light blue	- alcohol-based -	for water-free preparation
95015392	5 l	Light blue	- alcohol-based -	for water-free preparation
95015393	10 l	Light blue	- alcohol-based -	for water-free preparation
95001759	1 l	Red	- oil-based -	for water-free preparation
95001772	2.5 l	Red	- oil-based -	for water-free preparation
95001784	5 l	Red	- oil-based -	for water-free preparation

Information Diamond lubricant

Diamond lubricant can be applied for lubrication and dilution of concentrated diamond suspensions and diamond pastes on a polishing cloth. Additionally, they act as coolant during the polishing process.
When using Dia-Complete-Suspension no additional lubricant is needed.



Item No.	Unit	Description
Alumina suspension, calcinated		
		Description Grain Size
aqueous concentrate, to dilute, 3-5 part of dest. water		
92002533	1 l	Alumina suspension 0.3 µm
92002532	1 l	Alumina suspension 0.6 µm
92004950	1 l	Alumina suspension 1 µm

Fine polishing suspensions

Description Grain Size

Fine polishing suspension (Al₂O₃, Sol-Gel suspension)
 » does not crystallize
 » for ferrous materials, polymers, composites, PCB, rocks and minerals

92002534	1 l	Eposal, pH≈8.0 0.06 µm
----------	-----	-----------------------------

Colloidal silica

» for polishing, also mixable with diluted etchant
 » for ferrous and non-ferrous materials, especially soft materials like Al,Cu,Ti and solder joints

92002536	1 l	Eposil F, pH≈9.5 0.1 µm
95013858	1 l	Eposil Non Dry, pH≈9.5 0.05 µm
95013958	10 l	Eposil Non Dry, pH≈9.5 0.05 µm
92002541	1 kg	Eposil M, pH≈9.5 0.06 µm

Colloidal silica

» for titanium, nickel, zinc and its alloys

95001206	1 kg	Eposil M11, pH≈11 0.06 µm
----------	------	--------------------------------

Water-free fine polishing suspension

» e.g. for magnesium, tin

95005033	1 kg	Etosil E, pH≈7.0 0.06 µm
----------	------	-------------------------------

» Download of Safety Data Sheets at
<http://www.atm-m.com/products/consumables>



NEW



Item No.	Unit	Description		
GALAXY Polishing cloth with metal back				
		Description	Ø	Fixation
ALPHA – GALAXY Polishing cloth, magnetic very hard, perforated chemotextile cloth » long lifetime and stock removal » for ceramics, hard metal, steel, cast iron, aluminum, plastic » for pre-polishing » diamond 15/9 µm				
95001407	5 Pcs.	Alpha	200 mm	magnetic/adhesive carrier
95001408	5 Pcs.	Alpha	250 mm	magnetic/adhesive carrier
95001409	5 Pcs.	Alpha	300 mm	magnetic/adhesive carrier
95013994	5 Pcs.	Alpha	350 mm	magnetic/adhesive carrier
GALAXY Polishing cloth BETA				
hard synthetic cloth » material with high hardness » steel, cast, iron, hard metal, ceramics » for pre-polishing » diamond 15/9/6 µm				
95001410	5 Pcs.	Beta	200 mm	magnetic/adhesive carrier
95001411	5 Pcs.	Beta	250 mm	magnetic/adhesive carrier
95001412	5 Pcs.	Beta	300 mm	magnetic/adhesive carrier
95013995	5 Pcs.	Beta	350 mm	magnetic/adhesive carrier
GALAXY Polishing cloth PHI				
medium hard chemotextile cloth » ferrous and non-ferrous metals, minerals, ceramics, composites » for pre- and final polishing » diamond 9/6/3/1 µm, oxide polishing				
95012739	5 Pcs.	Phi	200 mm	magnetic/adhesive carrier
95012740	5 Pcs.	Phi	250 mm	magnetic/adhesive carrier
95012741	5 Pcs.	Phi	300 mm	magnetic/adhesive carrier
95014002	5 Pcs.	Phi	350 mm	magnetic/adhesive carrier
GALAXY Polishing cloth DELTA				
medium hard silk cloth » C-steels, precious metals, coatings, plastics, aluminum » for pre- and intermediate polishing » diamond 9/6/3 µm				
95001413	5 Pcs.	Delta	200 mm	magnetic/adhesive carrier
95001414	5 Pcs.	Delta	250 mm	magnetic/adhesive carrier
95001415	5 Pcs.	Delta	300 mm	magnetic/adhesive carrier
95013996	5 Pcs.	Delta	350 mm	magnetic/adhesive carrier
GALAXY Polishing cloth SIGMA				
soft wool cloth » for all materials » for intermediate and final polishing » diamond 9/6/3 µm				
95001416	5 Pcs.	Sigma	200 mm	magnetic/adhesive carrier
95001417	5 Pcs.	Sigma	250 mm	magnetic/adhesive carrier
95001418	5 Pcs.	Sigma	300 mm	magnetic/adhesive carrier
95013997	5 Pcs.	Sigma	350 mm	magnetic/adhesive carrier

Especially suitable for adhere carrier disc (page 40)



Item No.	Unit	Description		
GALAXY Polishing cloth with metal back				
		Description	Ø	Fixation
GALAXY Polishing cloth IOTA short-napped, soft synthetic cloth » for all materials, especially hard steels » for intermediate and final polishing » diamond 3/1 µm				
95001419	5 Pcs.	Iota	200 mm	magnetic/adhesive carrier
95001420	5 Pcs.	Iota	250 mm	magnetic/adhesive carrier
95001421	5 Pcs.	Iota	300 mm	magnetic/adhesive carrier
95013998	5 Pcs.	Iota	350 mm	magnetic/adhesive carrier
GALAXY Polishing cloth ZETA short-napped, soft synthetic cloth » for all materials » for final polishing » Alumina & oxide suspension » diamond 3/1 µm				
95005776	5 Pcs.	Zeta	200 mm	magnetic/adhesive carrier
95005777	5 Pcs.	Zeta	250 mm	magnetic/adhesive carrier
95005778	5 Pcs.	Zeta	300 mm	magnetic/adhesive carrier
95013999	5 Pcs.	Zeta	350 mm	magnetic/adhesive carrier
GALAXY Polishing cloth OMEGA soft synthetic cloth (chemically resistant) » for all materials » for final polishing » oxide suspension				
95005779	5 Pcs.	Omega	200 mm	magnetic/adhesive carrier
95005780	5 Pcs.	Omega	250 mm	magnetic/adhesive carrier
95005781	5 Pcs.	Omega	300 mm	magnetic/adhesive carrier
95014000	5 Pcs.	Omega	350 mm	magnetic/adhesive carrier
GALAXY Polishing cloth LAMBDA short-napped, structured synthetic cloth » for all materials » no suction of large samples » for final polishing » oxide suspension				
95005782	5 Pcs.	Lambda	200 mm	magnetic/adhesive carrier
95005783	5 Pcs.	Lambda	250 mm	magnetic/adhesive carrier
95005784	5 Pcs.	Lambda	300 mm	magnetic/adhesive carrier
95014001	5 Pcs.	Lambda	350 mm	magnetic/adhesive carrier

Especially suitable for adhere carrier disc (page 40)

Information about GALAXY Polishing cloths

Ready-to-use as polishing cloths are glued onto the metal (stainless steel) carrier.

The rigid back ensures optimal edge retention and enhanced reproducibility of the preparation results and prolongs the life time.

The lugs support easy handling when putting the Galaxy discs on or off the magnetic adhesive carrier.





Item No.	Unit	Description		
Polishing cloths, self-adhesive				
		Description	Ø	Fixation
		ALPHA – Polishing cloth, self-adhesive » very hard, perforated chemotextile cloth » long lifetime and stock removal » for ceramics, hard metal, steel, cast iron, aluminum, plastic » for pre-polishing » diamond 15/9 µm		
92002555	5 Pcs.	Alpha	200 mm	self-adhesive
92002564	5 Pcs.	Alpha	250 mm	self-adhesive
92002573	5 Pcs.	Alpha	300 mm	self-adhesive
95016029	5 Pcs.	Alpha	350 mm	self-adhesive
		Polishing cloth BETA hard synthetic cloth » for material with high hardness » for steel, cast, iron, hard metal, ceramics » for pre-polishing » diamond 15/9/6 µm		
95006571	5 Pcs.	Beta	200 mm	self-adhesive
95006572	5 Pcs.	Beta	250 mm	self-adhesive
95006573	5 Pcs.	Beta	300 mm	self-adhesive
95016030	5 Pcs.	Beta	350 mm	self-adhesive
		Polishing cloth PHI medium hard chemotextile cloth » ferrous and non-ferrous metals, minerals, ceramics, composites » for pre- and final polishing » diamond 9/6/3/1 µm, oxide polishing		
92005678	5 Pcs.	Phi	200 mm	self-adhesive
92005679	5 Pcs.	Phi	250 mm	self-adhesive
92005680	5 Pcs.	Phi	300 mm	self-adhesive
95016031	5 Pcs.	Phi	350 mm	self-adhesive
		Polishing cloth GAMMA medium hard silk cloth » for C-steels, non-ferrous metals, coatings, plastics (GRP, CFC) » for pre- and intermediate polishing » diamond 9/6/3 µm		
92002558	5 Pcs.	Gamma	200 mm	self-adhesive
92002567	5 Pcs.	Gamma	250 mm	self-adhesive
92002576	5 Pcs.	Gamma	300 mm	self-adhesive
95016032	5 Pcs.	Gamma	350 mm	self-adhesive
		Polishing cloth SIGMA soft wool cloth » for all materials » for pre- and intermediate polishing » diamond 9/6/3 µm		
92008810	5 Pcs.	Sigma	200 mm	self-adhesive
92008811	5 Pcs.	Sigma	250 mm	self-adhesive
92008812	5 Pcs.	Sigma	300 mm	self-adhesive
95016033	5 Pcs.	Sigma	350 mm	self-adhesive
		Polishing cloth DELTA medium hard silk cloth » for C-steels, precious metals, coatings, plastics, aluminum » for pre- and intermediate polishing » diamond 9/6/3 µm		
92008801	5 Pcs.	Delta	200 mm	self-adhesive
92008802	5 Pcs.	Delta	250 mm	self-adhesive
92008803	5 Pcs.	Delta	300 mm	self-adhesive
95016034	5 Pcs.	Delta	350 mm	self-adhesive



Item No.	Unit	Description
Polishing cloths, self-adhesive		
		Description Ø Fixation Polishing cloth EPSILON, short-nap, medium hard synthetic cloth » for all materials and very hard materials » for final polishing » diamond 3/1 µm
92004411	5 Pcs.	Epsilon 200 mm self-adhesive
92004412	5 Pcs.	Epsilon 250 mm self-adhesive
92004413	5 Pcs.	Epsilon 300 mm self-adhesive
95016035	5 Pcs.	Epsilon 350 mm self-adhesive
Polishing cloth IOTA		
		short-nap, soft synthetic cloth » for all materials, especially hard steels » for intermediate and final polishing » diamond 3/1 µm
95002393	5 Pcs.	Iota 200 mm self-adhesive
95002394	5 Pcs.	Iota 250 mm self-adhesive
95002395	5 Pcs.	Iota 300 mm self-adhesive
95016036	5 Pcs.	Iota 350 mm self-adhesive
Polishing cloth ZETA		
		short-nap, soft synthetic cloth » for all materials » for final polishing » for Alumina & oxide suspension » diamond 3/1 µm
92005681	5 Pcs.	Zeta 200 mm self-adhesive
92005683	5 Pcs.	Zeta 250 mm self-adhesive
92005684	5 Pcs.	Zeta 300 mm self-adhesive
95016037	5 Pcs.	Zeta 350 mm self-adhesive
Polishing cloth KAPPA		
		soft felt cloth » for final polishing » for Alumina suspension
92002563	5 Pcs.	Kappa 200 mm self-adhesive
92002572	5 Pcs.	Kappa 250 mm self-adhesive
92002581	5 Pcs.	Kappa 300 mm self-adhesive
95016038	5 Pcs.	Kappa 350 mm self-adhesive
Polishing cloth OMEGA		
		soft synthetic cloth (chemical resistant) » for all materials » for final polishing » for oxide suspension
92002562	5 Pcs.	Omega 200 mm self-adhesive
92002571	5 Pcs.	Omega 250 mm self-adhesive
92002580	5 Pcs.	Omega 300 mm self-adhesive
95016039	5 Pcs.	Omega 350 mm self-adhesive
Polishing cloth LAMBDA		
		short-nap, structured synthetic cloth » for all materials » no suction of large samples » for final polishing » oxide suspension
95003597	5 Pcs.	Lambda 200 mm self-adhesive
95003598	5 Pcs.	Lambda 250 mm self-adhesive
95003599	5 Pcs.	Lambda 300 mm self-adhesive
95016040	5 Pcs.	Lambda 350 mm self-adhesive
» all polishing cloths also available for Saphir 300 (Ø 30 mm)		





Item No.	Unit	Description
Polishing cloth carrier discs		
Ø		
» for adhere discs		
05610121	1 Pcs.	200 mm
05610123	1 Pcs.	250 mm
05610124	1 Pcs.	300 mm
» for magnetic system		
05610206	1 Pcs.	200 mm
05610208	1 Pcs.	250 mm
05610209	1 Pcs.	300 mm
» other diameter on request		
Carrier Plate		
Ø		
» for grinding and polishing robot SAPHIR X-Change		
95005867	1 Pcs.	250 mm
Magnetic foil, self-adhesive		
Ø		
» to apply on working wheel		
92008528	1 Pcs.	200 mm
92005820	1 Pcs.	250 mm
92005822	1 Pcs.	300 mm
95014137	1 Pcs.	350 mm
» other diameter on request		



Item No.	Unit	Description
Electrolytes (consisting of two components; total volume 1 litre)		
Description		
Electrolyte for stainless steel, aluminum, aluminum alloys and special materials » for electrolytic etching/polishing		
92002680	1 Pcs.	K1 - Part A, equals 1 litre in combination with Part B
92002980	1 Pcs.	K1 - Part B (perchloric acid), equals 1 litre in combination with Part A
Electrolyte for titanium		
92003011	1 Pcs.	T1 - Part A, equals 1 litre in combination with Part B
92003012	1 Pcs.	T1 - Part B (perchloric acid), equals 1 litre in combination with Part A
Electrolyte for grey iron		
92003014	1 Pcs.	F1 - Part A, equals 1 litre in combination with Part B
92003015	1 Pcs.	F1 - Part B (perchloric acid), equals 1 litre in combination with Part A » shipping of hazardous materials will be charged extra » Download of Safety Data Sheets at http://www.atm-m.com/products/consumables

Accessories for Kristall 650

Description

Electrolyte-bottle with screw top

95003955	1 Pcs.	Volume 1 litre
----------	--------	----------------

Accessories set for Kristall 650 in suitcase

Z6201001	1 Pcs.	Suitcase (single-order No.): » 5 pcs V-ring (Order No.: 95003606) » 1 pc profile ring material, appr. 150 mm (Order No.: 06201052) » 1 pc flexible end piece for profile ring (Order No.: 06201051) » 1 pc tube cutter (Order No.: 95004030) » 10 pcs filter pads Ø 40.5 mm (Order No.: 95003985) » 1 pc dolphin clamp (Order No.: 82000374)
----------	--------	--





Item No.	Unit	Description
Etchants		
Description		
95014346	500 ml	VisiPro-I Etchant for visualizing the former austenitic grain boundaries (for quenched or tempered low-alloy quenched and tempered steels and case-hardened steels)
95014347	1 l	VisiPro-I Etchant for visualizing the former austenitic grain boundaries (for quenched or tempered low-alloy quenched and tempered steels and case-hardened steels)
95014348	500 ml	VisiPro-II Etchant for visualizing the former austenitic grain boundaries (for quenched or tempered low-alloy quenched, tempered case hardening steels and anti-friction bearing steels)
95014349	1 l	VisiPro-II Etchant for visualizing the former austenitic grain boundaries (for quenched or tempered low-alloy quenched, tempered case hardening steels and anti-friction bearing steels)
95006393	1 l	Barker reagent (for Aluminum grain boundaries)
92002601	1 kg	Heyn Etchant (for steel, phosphorous segregations, macro etching, copper alloys, brass)
92002602	1 kg	Adler Etchant (for steel, weldings, macro etching)
92002603	1 l	Alcoholic picric acid, 5% Picral (for steel, martensite)
92002597	1 l	Alcoholic nitric acid, 3% Nital (for unalloyed and low alloyed steels)
92002596	1 l	Alcoholic nitric acid, 1% Nital (for unalloyed and low alloyed steels)
92002605	1 kg	V2A Etchant (for austenitic steels), application with approx. 60°
92002606	250 g	Additive for V2A-etchant
92002678	1 kg	Sodium hydroxide solution (for aluminum alloys)
92004240	1 kg	Oberhoffer Etchant (for steel, segregations, flow-lines, macro/micro etching)
92004492	1 kg	Kroll Etchant (for aluminum alloys, titanium)
92004493	1 kg	Fry Etchant (for steel, macro/micro etching, flow lines)
92004222	1 kg	CU2 etching fluid (copper, copper with sulfide and oxide inclusions)
92002750	1 kg	Sodium picrate (for cementite detection in steel)
95002313	1 l	Kalling 1 Etchant (for martensitic stainless steel)
95002347	1 kg	Kalling 2 Etchant (for nickel, nickel alloys, stainless steels, nickel-copper alloys)
95002434	1 l	Color etching according to Klemm I (for low carbon steels), stock solution
95002390	20 g	Potassium bisulfite for Klemm I
95002435	1 l	Color etching according to Klemm II (copper, solder joints), stock solution
95002391	50 g	Potassium bisulfite for Klemm II
95002436	1 l	Bechet-Beaujard Etchant, prior austenite grain boundaries
95002408	1 kg	Murakami Etchant (for hard metals, molybdenum/molybdenum alloys, chromium alloys, tungsten and tungsten alloys)
» shipping of hazardous materials will be charged extra » Download of Safety Data Sheets at http://www.atm-m.com/products/consumables		





Analyzing

Microscopy/Analysis



Accessories for microscopy	70
Iron-carbon-diagram	70
Cleaning agents for ultrasonic cleaner	71
Cleaning aids	71
Assembly cleaner	71

Accessories for Microscopy/Analysis



Accessories	72
Storage of samples	72
Safety equipment for etching	73
Pane cleaning for fume cupboard	73
Replication set	73
Precision replication material	73



Item No.	Unit	Description
Accessories for microscopy		
Description		
Supporting accessories		
92004109	1 kg	Plasticine
92002943	5 Pcs.	Microscope slides, metal, 76x26 mm
92004243	100 Pcs.	Microscope slides, glas, 32x24 mm
92004256	100 Pcs.	Microscope slides, glas, 40x24 mm
M1321000	1 Pcs.	Specimen press » for parallel fixation of specimen on microscope slide » comfortable operation with minimal effort » compact, robust and durable » made of aluminum with anodised surface

Item No.	Unit	Description
Iron-carbon-diagram		
Description		
Iron-carbon-diagram		
92008881	1 Pcs.	Standard format 700 x 700 mm
92008882	1 Pcs.	Heavy format 700 x 700 mm

Info hardness test blocks

Further information to our hardness test blocks on our website www.atm-m.com



Item No.	Unit	Description
Cleaning agents for ultrasonic cleaner		
Description		
Cleaning concentrate, alkaline » for universal use and intensive cleaning » use 1 – 5%, pH 10 at 2%, removes oils, fats, silicon oil residues, pigments, ink and proteins		
92002614	1 l	Tickopur R 33
Cleaning concentrate with ammonia, mildly alkaline, phosphate free » use 5 – 10%, removes oils, fats, waxes, pigments, silicon fats and grime (not suitable for aluminum)		
92002615	1 l	Tickopur RW 77
Cleaning aids		
Description		
95004662	1 l	Ethanol, 99% denatured
95004663	5 l	Ethanol, 99% denatured
95004664	10 l	Ethanol, 99% denatured
92004510	1 l	Aceton, chemically pure
Assembly cleaner		
Description		
» for sample preparation, for replication set, in spray can		
92004376	500 ml	Assembly cleaner spray
» additional fees can be necessary by shipping of hazardous materials » Download of Safety Data Sheets at http://www.atm-m.com/products/consumables		





Item No.	Unit	Description
Accessories		
Description		
92002779	100 g	Mounting adhesive 100 g, excellent bonding for metals and ceramics
92002630	200 g	Cotton wool
92008773	100 Pcs.	Specimen cleaning wipes
92004428	300 ml	Sample protection laquer, spray (conservation of samples)
92002629	1 Pcs.	Etching bowl, DURAN® glass with cover, heat-resistant, Ø 60/H 40 mm
92002628	1 Pcs.	Etching bowl, DURAN® glass with cover, heat-resistant, Ø 80/H 50 mm
92002430	1 Pcs.	Etching bowl, DURAN® glass with cover, heat-resistant, Ø 100/H 60 mm
92002626	1 Pcs.	Etching bowl, DURAN® glass with cover, heat-resistant, Ø 150/H 80 mm
95012078	1 Pcs.	Etching bowl, polyethylene (PE), Ø 90 /H 40 mm
95012079	1 Pcs.	Etching bowl, polyethylene (PE), Ø 110/H 55 mm
95012080	1 Pcs.	Etching bowl, polyethylene (PE), Ø 110/H 75 mm
95012081	1 Pcs.	Etching bowl, polypropylene (PP), Ø 60/H 60 mm
95012082	1 Pcs.	Etching bowl, polypropylene (PP), Ø 115/H 70 mm
92008770	1 Pcs.	Spray bottle, 250 ml
92002432	1 Pcs.	Spray bottle, 500 ml
92004491	1 Pcs.	Washing bottle with narrow neck, 500 ml
92004302	1 Pcs.	Measuring cylinder, 50 ml
92004303	1 Pcs.	Measuring cylinder, 100 ml
92002431	1 Pcs.	Crucible Tong, stainless
95008097	1 Pcs.	Crucible Tong, stainless with insulated handle
92004265	1 Pcs.	Specimen dryer, wall fastening model, with proximity sensor
A5810355	1 Pcs.	Specimen drying unit for set up on table



Desiccator cabinet (95012025)

Storage of samples

Description

Storage systems for readily prepared samples

92002898	1 Pcs.	Disc cabinet 320 x 320 mm, for discs Ø 300 mm with 6 drawers
92002717	1 Pcs.	Disc cabinet, 290 x 290 mm, for discs Ø 200 and 250 mm with 5 drawers
95012025	1 Pcs.	Desiccator cabinet 310 x 525 x 375mm
95012026	1 Pcs.	Shelf for desiccator cabinet
92002684	1 Pcs.	Desiccator, DM 250, with cover and basket, DURAN® clear glass
95002659	1 Pcs.	Desiccator, DM 150, with cover and basket, DURAN® clear glass
92002868	1 kg	KC-drying pearls, for use with desiccator
A7500417	1 Pcs.	Sample box, 320 x 320 x 58 mm for 56 Samples Ø 25-32 mm
A7500418	1 Pcs.	Sample box, 320 x 320 x 58 mm for 25 Samples Ø 38-50 mm



Item No.	Unit	Description
Safety equipment for etching		
Description		
Face protection shield according to DIN EN 166 1 3 - S complete protection of face, unlimited field of view, acids and bases » resistant, robust plastic material, shatterproof, scratch-resistant		
95002951	1 Pcs.	Face protection shield
Protective laboratory apron » made of PVC, with neck and side bonds, clean edges, without fabrics		
95004848	1 Pcs.	Protective Laboratory Apron, 900 x 1100 x 0.5 mm
Nitrile gloves (single use), conforms to EN 420, EN 374		
95008893	100 Pcs.	Nitrile gloves, conforms to EN 420, EN 374, size M
95007658	100 Pcs.	Nitrile gloves, conforms to EN 420, EN 374, size L
95008208	90 Pcs.	Nitrile gloves, conforms to EN 420, EN 374, size XL
Safety goggles conforms to EN 166, length-adjustable		
92005963	1 Pcs.	Safety goggles conforms to EN 166
Pane cleaning for fume cupboard		
Description		
Pane cleaning set in suitcase		
Z7510002	1 Pcs.	» Pane wiper magnet » 2x 30 pcs. cleaning cloths
95006797	1 Pcs.	Pane wiper magnet
95006798	30 Pcs.	Cleaning cloths for glass
Replication set		
Description		
Replica system for non-destructive analyzing of microstructures quick cured 2 components compound for applying to surfaces; the cured replica can be removed easily and analysed directly		
92006498	2x50 ml	2-components-compound
92006609	1 Pcs.	Dosing gun
92008692	48 Pcs.	Mixing tube
Precision replication material		
Description		
Replica system for surface structures (metallic or mineral), for surface roughness inspection (R, Ra)		
95001664	900 ml	2-components-compound standard
95001665	900 ml	2-components-compound soft



ATM GmbH, Germany, General Terms and Conditions of Business and Delivery

1. General remarks

- 1.1 Deliveries and services are performed exclusively on the basis of the following General Terms and Conditions of Delivery. They form a component of all contracts entered into and also apply to all future business relationships, even if they are not expressly agreed again.
- 1.2 The Customer acknowledges these General Terms and Conditions when it places an order, and no later than upon acceptance of the delivery or service.
- 1.3 Any contrary terms and conditions or divergent counter-confirmations from the Customer will have no binding effect on us, even if we do not expressly object to them. They require our express written acknowledgement to take legal effect.
- 1.4 Any addenda, amendments or ancillary agreements require our written confirmation to take legal effect. The same applies to the revocation of the written form requirement.

2. Offer and conclusion of contract

- 2.1 Catalogues, promotional brochures, price lists, cost estimates and offers are subject to confirmation and non-binding. All documents in this respect, such as drawings, typical analyses, dimensional data etc. are to be treated as approximate unless expressly designated as binding. We reserve our right of ownership and copyright to catalogues, drawings, cost estimates and other documents; and they may not be made available to third parties.
- 2.2 The Customer is liable for the correctness and completeness of specified dimensions and Customer samples as well as the correctness of documents to be provided by it, which include drawings, instructions, samples and the like as well as other information that affects the suitability of the items ordered for the intended application. The Customer is further liable for any infringement of third-party patent rights or intellectual property rights arising from the use of these documents. In that respect the Customer will indemnify us against any liability claims brought by third parties. We are not obliged to check whether the execution of any documents provided to us in this capacity infringes any third-party rights.
- 2.3 Material samples or Customer samples are to be delivered to us by the Customer free of charge. We may destroy any material samples submitted unless an express request for their return is made at the time of their delivery or within four weeks of us receiving them. The party submitting the material samples is liable for all risks associated with their transportation, storage and processing. This applies in particular to any damage that the material sample causes itself or in combination with any substances with which it comes into contact (toxic, corrosive, explosive materials), unless liability under clause 10.1 applies. We will invoice the analysis of material samples on the basis of the effective applicable hourly rates. If the analysis leads to a sale, the analysis costs will be offset against the purchase price.
- 2.4 The contract will only come into force when we provide written confirmation of the order and in accordance with the content of this confirmation, or upon acceptance of the delivery by the Customer. If no written confirmation is made, our delivery notes or invoices will additionally serve as order confirmations.
- 2.5 We reserve the right to make technical modifications to the subject matter of the contract during the delivery period, including after issue of the order confirmation, provided this is reasonable for the Customer balanced against our interests in the modification. The same applies to standard industry variations in weights and measures.
- 2.6 Spoken promises by and arrangements with our employees shall only bind us to the extent that these have been confirmed by us.

3. Deliveries

- 3.1 The delivery times set out in the order confirmations are non-binding, approximate information. They are only binding if we have expressly designated them as binding.
- 3.2 The delivery period commences with the date of the written order confirmation; if, at this time, there are any outstanding issues requiring clarification, the delivery period only commences after all such issues have been clarified. If advance payments have been agreed, the delivery period does not start until receipt of the first payment.
- 3.3 The delivery period will be deemed to have been complied with if the item to be delivered has left our plant or readiness for dispatch has been communicated before or on the date of expiry of the agreed delivery period.
- 3.4 In justified exceptional cases, and in particular for operational reasons, part deliveries and part services may be performed subject to advance notice. These will be invoiced separately.
- 3.5 We will not be liable for any delays to deliveries and services due to force majeure or other events over which we have no influence and for which evidence that they affect the completion or delivery of the subject matter of the delivery can be adduced – these include strike, lock-out, official directives, material shortages, non-availability or non-deliverability of goods etc. – including such circumstances affecting our own suppliers, even where binding periods and dates have been agreed and also during any period of default. We will notify the Customer of the commencement and termination of such hindrances without undue delay. In the event of temporary impairments, we are entitled to postpone the deliveries or services for the duration of the hindrance plus a reasonable lead time. Should performance become permanently impossible, we have the right to withdraw from unfulfilled part of the contract in full or part. The Customer may demand a declaration from us as to whether we intend to withdraw from the contract or deliver within a reasonable period. If we do not provide such a declaration and the Customer feels that it is unreasonable to expect it to accept delivery due to the delay, the Customer may withdraw from the contract.
- 3.6 The Customer bears sole responsibility for the suitability of the installation location for the supplied goods, for procurement of all necessary permits and for compliance with all planning, building and company regulations as well as for the preparation of the installation location, including the erection of any necessary foundations and the performance of all preliminary work necessary for the delivery and assembly or installation of the goods. The Customer also bears sole responsibility for the availability of the installation location with the necessary lifting and installation tools.
- 3.7 Our performance is subject to correct and timely delivery to us by our suppliers at all times. This reservation regarding correct and timely delivery by our suppliers is subject to the proviso that we entered into a corresponding covering transaction in good time and/or we are not responsible for the delayed delivery by our suppliers.
- 3.8 If we are responsible for not meeting agreed binding deadlines or dates, or we are in default of delivery/service, the Customer is entitled to withdraw from the contract after the expiry of an appropriate grace period; any further obligation to pay compensation is governed under clause 10 of these General Terms and Conditions.
- 3.9 If the Customer is in default in acceptance, we are entitled to demand compensation for non-performance in the amount of 15% of the agreed order value, without prejudice to the option to prove a greater loss. This is subject to an appropriate grace period being set along with a notice of potential rejection and subsequent withdrawal from the contract. For its part, the Customer reserves the right to provide evidence that no loss was sustained, or that the loss was substantially lower. In the case of Customer-specific products and/or systems, the loss is in principle the contract value less any advance payments made. The option to provide evidence of a higher or lower loss is reserved.

4. Shipping and transfer of risk

- 4.1 The place of performance for delivery is the location of our respective dispatching plant (INCO terms as amended from time to time: FCA dispatching plant).
- 4.2 Shipping is always performed at the Customer's own risk, including where partial shipments are made or we are rendering other services such as payment of shipping costs or carriage.
- 4.3 In the absence of any specific instructions, packaging and the selection of the transport route and means of transport is at our discretion. If the goods are accepted by the rail company, postal service, freight carrier or other transport company with no objections, this serves as a

confirmation that the packaging is in a flawless condition on dispatch and excludes any liability on our part for any damage or loss incurred en route due to improper packaging or loading, unless we are subject to strict liability for intentional misconduct or gross negligence.

- 4.4 The risk of accidental destruction or accidental deterioration of the goods passes to the Customer no later than at the point of handover of the goods to the haulier, the railways or other freight carrier, and no later than on dispatch from our warehouse or, in the case of direct delivery, on dispatch from our dispatching plant – e.g. also for CPT and CIP transactions. If the goods are to be collected by the Customer, the risk passes to the Customer on issue of the notification informing the Customer that the goods are ready for collection.
- 4.5 Any goods accepted prior to dispatch are deemed delivered pursuant to the agreed terms.
- 4.6 If dispatch or acceptance is delayed at the Customer's request or for reasons for which it is at fault, the risk of accidental destruction or accidental deterioration passes to the Customer on the date when we communicate the first and initial notification of readiness for dispatch or notification of acceptance in writing or verbally. In this case we are entitled to charge storage costs of 1.0% of the invoice amount for each month of the delivery delay, starting one month after notification of readiness for dispatch. The Customer reserves the right to furnish proof that no costs were sustained, or that the costs were substantially lower.
- 4.7 In the event of a delay in acceptance by the Customer, we may assert our right under clause 3.9 or freely dispose of the item or items for delivery and supply an equivalent item or items at the contract terms instead.
- 4.8 We are entitled to insure the transport risk and invoice these costs to the Customer unless the Customer instructs otherwise in writing.

5. Prices and payment terms

- 5.1 Prices are quoted on a strictly net basis ex works or ex warehouse, including the costs of packaging, but net of insurance, export/import or other supplementary costs – and exclusive of VAT at the applicable rate.
- 5.2 If the conclusion of the contract and the date of delivery are more than four months apart, we may invoice the prices applicable on the date of delivery, unless otherwise agreed. If this is more than a minimal price increase, the Customer may withdraw from the contract.
- 5.3 Increase of wages, procurement prices, freight costs, taxes, charges or other costs that result in price increases between the conclusion of the contract and delivery, or the emergence of equivalent new, unforeseen costs, entitle us to adjust the purchase price accordingly to the extent permissible by law.
- 5.4 After conclusion of the contract we are entitled to request a deposit of a reasonable amount. In the case of Customer-specific systems/apparatus, this will be at least 50% of the contract value.
- 5.5 In the absence of any other express agreement, payment will fall due on receipt of the invoice. Payments are to be made strictly net no later than 30 days after the invoice date. For Customer-specific systems/apparatus at least 50% of the order value will fall due with the request for a deposit. The rest will be invoiced on issue of the notification of readiness for delivery and is payable immediately.
- 5.6 In the case of default we are entitled to charge interest at the level of interest for commercial loans calculated by our company bank, and no less than interest of 5 percentage points above the base rate applicable on the day on which the event of default commenced (EURIBOR). The Customer reserves the right to provide evidence that no loss was sustained, or that the loss was substantially lower. We reserve the right to assert further claims for damages resulting from delayed payment.
- 5.7 All of our receivables are payable immediately including where bills of exchange or cheques have been presented, if the terms of payment are breached without justification or we become aware of a substantial deterioration in the Customer's asset position after the contract is concluded. We are entitled to perform any deliveries and services outstanding at that point only against advance payment(s) or security deposit(s) or to reduce or cancel any assured commercial loans. If no advance payment(s) or security deposit(s) have been made on expiry of a reasonable grace period, we are entitled to withdraw fully or partly from the contract. In such a case we expressly reserve the right to assert claims for any expenditure incurred unnecessarily, loss of profits and other losses.
- 5.8 The Customer is only entitled to assert a right of set-off or retention, including in claims for defects or counterclaims, if the counterclaims are undisputed or established at law.

6. Commissioning Customer-specific systems/apparatus

- 6.1 Compliance with the agreed service features is always inspected at the place of manufacture.
- 6.2 If our services include assembly and commissioning, the Customer is required to prepare all installations, facilities and/or other factors necessary for the assembly of the system and its proper commissioning in full and in good time unless these preparatory tasks are included in our scope of services under an express written agreement. In this respect the duties set out at clause 3.6 also apply.
- 6.3 The provision at 6.2 notwithstanding, the Customer will be liable for the following during assembly and commissioning:
 - a) that our employees can commence their work as soon after their arrival as possible and can perform their tasks expeditiously during regular working hours and, if we deem such to be necessary, also outside regular working hours;
 - b) all statutory stipulations and safety regulations are complied with and the necessary facilities for the performance of the installation work are available;
 - c) the access routes to the installation location are suitable for deliveries to be performed;
 - d) the planned location for the assembly and operation of the system is suitable;
 - e) the necessary lockable storage facilities for material, tools and other accessories are available and accessible;
 - f) other auxiliary personnel, additional standard tools, industrial auxiliary materials (e.g. fuel, oils and lubricants, cleaning and other incidentals, gas, water, electricity, compressed air, heating, light etc.) and the Customer's standard measuring and test equipment are available promptly and at no charge;
 - g) the goods and products delivered by us for the assembly are at the correct location at the beginning of and during the assembly work.
- 6.4 The Customer bears sole liability for the risk of a breach of the duties set out at clause 6.3.

7. Retention of title

- 7.1 We reserve title to all goods supplied by us until the Customer has settled all claims arising under the business relationship, including any future claims from contracts entered into at the same time or subsequently, from any current account balance as well as until the absolute release from any contingent liabilities entered into in the Customer's interest.
- 7.2 The Customer must handle and store any goods subject to the retention of title with care and perform any standard inspection, servicing and maintenance work required at its own expense. The Customer may neither pledge the goods subject to the retention of title nor transfer them by way of security during the period of retention of title. Any access to the goods subject to the retention of title by third parties, for example by way of pledging or confiscation, as well as any damage or destruction must be reported to us in writing without undue delay.
- 7.3 If the Customer acts in a manner that is in breach of contract, in particular in the case of delayed payment of securitised claims, we are entitled to repossess the goods subject to the retention of title. Such repossession only represents a withdrawal from the contract if we confirm this in writing. Following repossession we are entitled to sell the goods and the proceeds will be set off against the Customer's liabilities after deduction of reasonable sales expenses.
- 7.4 a) The Customer is entitled and authorised to sell the goods subject to the retention of title in the course of ordinary business, which does not include what is known as the cheque-bill-of-exchange procedure. If the Customer is in default in respect of payments arising under the

business relationship with us, we may forbid that the goods be sold on. If the Customer allows its purchaser delayed payment of the purchase price, it may only sell the goods on if it, too, retains title to the goods sold.

- b) The Customer hereby assigns to us the purchase price claims or other claims for consideration accruing to it against its purchaser under the selling-on of the goods or other selling business including all ancillary rights. These serve as security to the same extent as the goods subject to the retention of title. The Customer is only entitled and authorised to sell on or otherwise dispose over the goods subject to the retention of title if it has been established that the claims arising thereunder are transferred to us, and in particular that no prohibition on assignment exists between the Customer and its purchaser.
 - c) If the Customer sells the goods subject to the retention of title along with other goods not supplied by us, the assignment of the claim from the sale only applies to the level of the invoice value of the respective goods subject to the retention of title sold. Where goods in which we have a co-ownership share are sold, the claim will be assigned to the value of this co-ownership share. If the assigned claim is included in a current account, the Customer hereby assigns to us a proportion of the balance corresponding to this claim – including a corresponding share of the closing balance – from the current account. If an interim balance is drawn up and it is agreed for this to be carried forward, the claim accruing to us per se under the foregoing provision is to be treated as if assigned to us for the purposes of the next balance.
 - d) The Customer is authorised to collect the claims assigned to us until we revoke such authorisation. We may not exercise this right of revocation as long as the Customer fulfils its payment obligations under the business relationship with us and provided we do not become aware of any circumstances which might substantially reduce the Customer's creditworthiness. If the prerequisites for exercising the right of revocation apply, we may request that the Customer assign to us any claims for surrender vis-à-vis its purchaser or notify us of the assigned claims and their debtors, provide all information necessary for collecting these claims, hand to us the associated paperwork and notify the debtors of the assignment. Additionally, we are authorised to give notice of the assignment to the debtors.
- 7.5 The Customer is entitled to process the goods subject to the retention of title in the ordinary course of its business, provided it is not in default of payment. Where the goods subject to the retention of title are processed or remodelled, we will be deemed the manufacturer of the newly created goods without being subject to any obligations. The processed or remodelled goods are deemed goods subject to the retention of title as set out at clause 7.1. Where the Customer processes the goods subject to the retention of title in combination with other items not belonging to us, we acquire co-ownership in the new item in the proportion of the value of the goods subject to the retention of title to the total value of the other items used; the time of processing is authoritative. If the goods subject to the retention of title are mixed, blended or combined with other items, and as a consequence our ownership of the goods subject to the retention of title is extinguished, the Customer hereby transfers to us the rights of ownership of the mixed or combined items accruing to it, or of the unified item in the proportion of the value of the goods subject to the retention of title to the total values of the other mixed, blended or combined items; the time at which the event occurs is authoritative. The Customer will also store the items co-owned by us under the foregoing provisions at no cost to us. The co-ownership shares arising under this clause are subject to the provisions of the whole of clause 7. in the context of goods subject to the retention of title.
- 7.6 At our request the Customer is obliged to provide information on the whereabouts of the goods subject to the retention of title at any time and on any claims arising from the selling-on of the goods or other further disposal.
- 7.7 Should the value of the existing security assigned to us exceed the secured claims by a total of more than 10%, we are obliged, if requested by the Customer, to release securities of our choosing to the same level.
- 7.8 If the retention of title set out in the foregoing provisions is not legally valid under the law of the country in which the goods subject to the retention of title are located, such security as most closely resembles this and is allowed under the law of this country will be deemed agreed. If the Customer is required to act in this context, the Customer is required to perform such acts at our request.
- ## 8. Warranty
- 8.1 The Customer must inspect the delivered goods upon receipt, and no later than within ten working days, for defects and, if agreed, to examine any guaranteed characteristics and report any identified defects without undue delay, and no later than within a further five working days. Where goods are delivered, the goods must be inspected immediately on receipt in respect of transport and packaging damage as well as variations in terms of quantity and dimensions. Any variations must be noted on the bill of lading or delivery note. Concealed defects must be reported in writing as soon as they are discovered. If the Customer fails to report defects within the stipulated time, the goods will be deemed defect-free and contractually compliant. In terms of quality, only our description of services in the order confirmation or the manufacturer's product description is deemed agreed. Public statements, testimonials or advertisements do not count as contractually binding information about the quality of the goods. Any deviations from an instruction manual, specification or other functionality described in the contract will only be recognised as a defect if they result in a substantial impairment of use. We must be notified of any returns in advance. The rectification of defects caused by normal wear and tear, other influences or operator error are excluded from the warranty unless covered by binding statutory claims. The same applies to any defects arising that are attributable to a modification of the goods not performed by us. We provide no warranty that the products supplied correspond to the Customer's specific application scenarios, or work together with other of the Customer's goods, or other manufacturers' goods, without failure or impairment. We accept no liability for advisory obligations. Consequently, any liability for assisted calculations, recommendations, suggested solutions etc. which are dependent on the Customer's systems or relate thereto is excluded.
- 8.2 The Customer has a right to subsequent performance for defective products by way of rectification of the defect or delivery of a defect-free replacement item at our discretion. If subsequent performance is unsuccessful, the Customer may choose to demand either a reduction in the consideration or the rescission of the contract. In the event of a minor contractual breach, in particular minor defects, the Customer will have no right of rescission. If the Customer exercises its right to rescission following unsuccessful subsequent performance, it has no additional claim to compensation due to the defect. If the Customer brings any claims for compensation following unsuccessful subsequent performance, the Customer will retain the goods if it is reasonable for it to do so. The claim for compensation is limited to the difference between the purchase price and the value of the defective goods. This does not apply if we breached the contract in bad faith. We may choose whether to render the subsequent performance at the place of installation or at our head office. If the subsequent performance is rendered at the place of installation, the Customer must provide our representative with unrestricted access to the purchased item both as regards time and place of access. Clause 6.3 applies in this respect. The Customer may further demand that warranty work is only performed during the regular business hours for the respective location. If the Customer requests that we perform warranty work outside our regular business hours, the Customer must pay any additional costs.
- 8.3 In the event of third party products, our liability is limited to the assignment of the warranty claims against our own supplier accruing to us. The warranty period is limited accordingly to the term that we are granted by our own supplier.
- 8.4 Warranty claims will expire within 24 months from the transfer of risk or the acceptance of the service. The warranty period relates to goods deployed in a laboratory that operates a single shift. If multiple shifts are worked, this period will be reduced accordingly to a minimum of twelve months. For repairs and spare parts the warranty period is limited to twelve months.
- 8.5 The foregoing paragraphs contain the full extent of the warranty for our products and goods. Any

further liability is governed solely by the provisions in clause 10. of these General Terms and Conditions.

- 8.6 The Customer is liable for the proper disposal of the supplied goods after the cessation of use in accordance with statutory provisions and at its own expense. The Customer will relieve the supplier of the statutory duties to take back old appliances and associated third party claims. If the Customer passes the supplied goods on to commercial third parties, it must impose on that party a contractual duty to properly dispose of the goods after the cessation of use in accordance with the statutory provisions and at that party's expense and to impose a corresponding obligation on any further parties to which the goods pass. If the Customer fails to do so when passing goods to a third party, it is obliged to take back the goods at its expense after the cessation of use and to properly dispose of them in accordance with the statutory provisions. The manufacturer's claim for the Customer to take on the goods and relieve it from its obligations will not expire until two years after the Customer ultimately ceases to use the appliance. The two-year period during which expiry is postponed begins no earlier than upon written notification by the Customer to the manufacturer regarding the cessation of use.

9. Software

- 9.1 The warranty for software is based on the above provisions in clause 8 with the following modifications: We will provide a warranty for the compliance of the software provided to the purchaser with our program specifications provided the software was installed on the systems envisaged by us in accordance with our stipulations. The warranty only covers software defects that can be readily reproduced. We undertake to rectify all non-insubstantial defects affecting usage in accordance with the contract; however, we reserve the right to select the method of rectification (installation of an improved software version or instructions on working around the defect).
- 9.2 The Customer is granted a non-exclusive and non-transferrable usage right over programs and associated documentation that are required for proper and internal use of the delivered product. The purchaser will accrue no further rights to programs and documentation, and in particular we will remain the copyright holder. The Customer is not permitted to provide third parties with access to programs, documentation and any subsequent amendments, or to copy, otherwise reproduce, decompile, disassemble or reverse-engineer such without our prior written consent.

10. Liability

- 10.1 We accept liability for any losses attributable to wilful misconduct or gross negligence on the part of our statutory representatives or vicarious agents or where contractually assured warranties or qualities of the goods that are intended to safeguard the Customer against atypical risks of loss are missing. In the case of ordinary negligence, we will only accept liability if material contractual duties are breached or if insurance cover is in place, and this will be limited to loss that was foreseeable at the time when the contract was entered into. No liability will be accepted for any further consequential losses. In particular, liability for any direct or indirect loss of any kind other than that set out here, including consequential loss, loss of use, income or profits and futile expenditure, additional expenditure and third-party claims is expressly ruled out, including in cases of negligence.
- 10.2 Liability is excluded in the case of defects caused by external factors such as voltage fluctuations, improper installation, wear and tear, operation and use/ maintenance/ changes to the goods by the Customer or third parties commissioned by the Customer, irrespective of the legal grounds.
- 10.3 In the absence of agreements to the contrary, any fixed compensation claims will be limited to a maximum of 5% of the purchase price.
- 10.4 The above limitations of liability have no bearing on any claims brought by the Customer under product liability legislation. Furthermore, the limitations on liability do not apply to personal injury, damage to health or death of the Customer or its vicarious agents and other third parties attributable to us.

11. Intellectual property rights and copyright

- 11.1 The products, all specifications, drawings, descriptions and illustrations are protected by intellectual property rights by the seller and subject to an obligation of confidentiality, unless they have been or will be published by the seller. The buyer will not disclose this information to anyone, except for the purpose of using the products in the course of its business.
- 11.2 The sale of the products does not bestow on the purchaser any rights or licences under any patent, industrial design or copyright, except for non-exclusive use of the product in the course of its own business.
- 11.3 If a third party brings a justified claim against the Customer due to the breach of an intellectual property right or copyright (hereinafter referred to as Protective Rights) due to the goods supplied by us or the contractually compliant use thereof, we will only be liable to the Customer subject to the following conditions:
- We will choose, at our expense, either to obtain a usage right for the goods, to modify the goods such that the Protective Right is not infringed or replace the goods. If this is not possible at reasonable terms, we will take the goods back and refund the purchase price.
 - The obligations set out above shall only apply if the Customer notifies us of any claims brought by third parties in writing and without undue delay, does not acknowledge a breach of the Protective Rights to the third party and reserves all defensive measures and settlement negotiations for us. Should the Customer cease to utilise the product owing to loss mitigation or other significant reasons, the Customer will point out to the third party that the cessation of utilisation is no acknowledgement of any infringement of any Protective Rights.
- 11.4 If the use of the product causes a breach of a patent, industrial design or copyright and if this breach is based on designs, specifications or instructions made by the purchaser, on the operation of the system by the purchaser in which the products are included, or manufacturing processes applied thereto, the purchaser will defend the claim, which must be notified to it without undue delay, at its own expense or to settle the claim by mutual agreement and to reimburse all losses and costs incurred by the seller as a result of such breach. This also applies if the infringement of the Protective Right is caused by an unforeseeable application on the part of the buyer or due to the products being modified or deployed with products not supplied by us. Any further claims against us will not be acknowledged. This does not apply e.g. where mandatory liability exists due to product liability, wilful misconduct, gross negligence or the infringement of material contractual obligations. The Customer also retains the right to withdraw from the contract under the foregoing provisions.

12. Closing provisions

- 12.1 The place of jurisdiction for deliveries and payments (including actions on cheques and bills of exchange) as well as all disputes arising between the parties is the competent court for Altenkirchen, Germany. However, we reserve the right to bring a claim against the Customer at any other place of jurisdiction permitted by law. The relationship between the contracting parties is governed solely by the law applicable in the Federal Republic of Germany. The UN Convention on Contracts for the International Sale of Goods (CISG) does not apply.
- 12.2 The Customer may only transfer the rights and obligations arising under this contract to third parties with our written consent. Such consent is not required if the assignment is made in the course of an effective extended retention of title that the Customer has agreed with a third party under the provisions of clause 7.
- 12.3 If individual provisions of these terms and conditions or parts thereof become invalid, this will have no bearing on the validity of the remaining provisions. An invalid provision of these terms and conditions will be replaced by a valid provision that most closely corresponds to the commercial intent of the invalid provision.

Expiry date of consumables

	Product	Expiry date
		Year(s)
Cutting	Abrasive cut-off wheels	2
	CBN cut-off wheels	2
	Diamond blades	2
	Cup grinder	2
	Coolant	2
	Additives for coolants	2
	Filter fleece & filter bags	2
Hot Mounting	Bakelite	2
	EPO-Max	2
	EPO black	2
	Duroplast	2
	Thermoplast	2
Cold Mounting	Methacrylate z.B. KEM 15+, 20, 30, 35, 60	1
	Epoxy resin KEM 90	1
	Mounting moulds	2
	Releasing agent	2
Grinding/Polishing	Grinding wheels	2
	GALAXY Diamond grinding discs	2
	SiC grinding foils	1
	SiC grinding paper without self-adhesive back/with foil back	2
	SiC grinding paper self-adhesiUnits	1
	SiC grinding belts	1
	Adhesive foil double-side	1
	Adhesive carrier	2
	Diamond suspensions	2
	Diamond paste	2
	Diamond spray	2
	Aluminum oxide suspensions (Alumina, Eposal)	2
	Colloidal silica	2
	Polishing cloths	2
	Polishing cloth carrier discs	2
	Magnetic foil	2
Etching	Etchants & electrolytes	1
Miscellaneous	Ethanol & Aceton	2
	Ultrasonic cleaning agents (Tickopur)	2
	Replication material Provil Novo	1

Remarks

„The listed expiry dates represent the minimum shelf life of the ATM consumables. Within this period the complete functionality of the products are guaranteed.

Reaching the expiry date does not cause a loose of the functionality of the products. Consequently, they can be used further more.

To ensure full functionality of the products, an **adequate storage** is essential. The products need to be reliably protected against humidity and temperature fluctuation.

When outside temperatures are high, delivery of the liquids of KEM 15, 20, 30, 35 and 60 is restricted. For further information please consult the data sheet.

The consumables and their packaging should not be opened unless for imminent use e.g. cut-off wheels are hygroscopic and cold mounting materials might react with oxygen).

This might influence the functionality over time.

The **expiry date starts from shipping date**.

Complaints are checked by our quality management and application team.

Our general terms and conditions remain unaffected from these notes.“



ADVANCED MATERIALOGRAPHY

Sign up for our newsletters!

You will occasionally receive exclusive information on seminars/webinars, applications and product news.

Subscribe now:



www.atm-m.com/newsletter
(You may unsubscribe any time)



Seminare & Schulungen

Guten Tag,
mit diesem Newsletter möchten wir Sie über Seminare & Schulungen bei und mit Unterstützung von ATM informieren.
Mit besten Grüßen
ATM GmbH - Advanced Materialography

Schulungen in der ATM-Akademie



Für 2018 sind noch einige wenige Plätze in unseren Seminaren "Einführung in die Materialographie und deren Arbeitsschritte" Teil 1 + 2 sowie "Grundlagen der Schweißtechnik in Theorie und Praxis" frei. Bringen Sie Ihre Kenntnisse auf den neuesten Stand und profitieren Sie von den Erfahrungen unserer langjährigen Referenten.

NEU: Untersuchungsmethoden für die Metallurgie

Zusammen mit CAROLTE GERO, ELTRA, REITSCH und SPECTRO veranstalten wir ein Sonderseminar mit dem Schwerpunkt "Untersuchungsmethoden für die Metallurgie für Einsteiger und Anwender" in Haan. Dieses Seminar umfasst die Themen Probenaufbereitung und Probenhomogenisierung, Elementaranalytik, Röntgenfluoreszenzanalyse und Funken-DEA, Lotbinde- und Sinterprozesse, additive Fertigung und die materialografische Probenpräparation. Wenn Sie die Möglichkeit, mitgebrachte Proben aufzubereiten und sich mit den Spezialisten auszutauschen.

- 10.09.2018 in Haan (bei Düsseldorf)
- Die Teilnahme an den Seminaren ist kostenlos, die Teilnehmerzahl jedoch begrenzt. Detaillierte Informationen zu den Seminaren und zur Online-Anmeldung finden Sie hier:

Applikationslabor in Nellingen

Unser ATM Applikationslabor Nellingen bei Stuttgart steht für Sie auf Basis unserer jahrzehntelangen Erfahrung in der Materialographie zur Verfügung.

Für unsere Kunden im südlichen Teil von Deutschland, der Schweiz und Österreich ist das Applikationslabor in Nellingen sehr komfortabel zu erreichen. Unseren wir fachkompetente Beratung, Probenaufbereitung Ihrer Werkstoffe an.

Wir erarbeiten mit Ihnen gemeinsam eine Lösung - vereinbaren Sie einen Termin für eine Probenaufbereitung in Nellingen für Sie.

Am 12. September 2018 ist unser Labor in Nellingen für Sie neu eröffnet. Detaillierte Informationen finden Sie in Kürze auf unserer Website.



ADVANCED MATERIALOGRAPHY

ATM GmbH

Emil-Reinert-Str. 2
57636 Mammelzen
Germany

Phone +49(0)2681/9539-0
Fax +49(0)2681/9539-20
E-Mail info@atm-m.com
Internet www.atm-m.com

part of **VERDER**
scientific

